CT49021N022 Details PDF



CT49021N022

Part Number:
Manufacturer/Brand:
Product description
Datasheets:
RoHs Status
Stock Condition
Ship From
Shipment Way

CT49021N022 APEM Inc. SWITCH TOGGLE DPDT 10A 125V PDF CT49021N022.pdf 💒 Lead free / RoHS Compliant 4115 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

Specifications of CT49021N022

ANUFACTURERAPEM Inc.DESCRIPTIONSWITCH TOGGLE DPDT 10A 125VDESCRIPTIONLead free / RoHS CompliantDEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantQUANTITY AVAILABLE4115 pcsDATA SHEETGC 149021N022.pdf/OLTAGE RATING - DCSolder, Quick Connect - 0.250" (6.3mm)/OLTAGE RATING - ACOn Off-OnSWITCH FUNCTIONOn Off-OnSWITCH FUNCTIONGroular - 12.20mm DiaSWITCH FUNCTIONGroular - 12.20mm DiaSWITCH FUNCTIONGroular - 12.20mm DiaSWITCH FUNCTIONGroular - 0.250" (6.3mm)SWITCH FUNCTIONGroular - 0.250" (6.3mm)SWITCH FUNCTIONGroular - 12.20mm DiaSWITCH FUNCTIONGroular - 12.20mm DiaSWITCH FUNCTIONGroular - 12.20mm DiaSWITCH FUNCTIONGroular - 0.250" (6.3mm)APACKAGINGBulkODTHER NAMESGroular - 12.20mm DiaAPACKAGINGHoldAPACKAGINGGroular - 12.20mm DiaADUNTING TYPEGOLDADUNTING TYPEGOLDADUNTING TYPEGOLDCLUMINATION VOLTAGE (NOMINAL)-ELUMINATION VOLTAGE (NOMINAL)-ELUMINATION TYPE, COLORGold - FullyELUMINATION TYPE, COLORJONO CYClesELUMINATION TYPE, COLORIDA (AC), 15A (DC)ELUMINATION TYPE, COLORIDA (AC), 15A (DC)ELUMINATION TYPEDIA (AC), 15A (DC)ELUMINATION TYPEIDA (AC), 15A (DC)ELUMINATION TYPEIDA (AC), 15A (DC)ELUMINATIO		
DescriptionSWITCH TOGGLE DPDT 10A 125VEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantQUANTITY AVAILABLE4115 pcsDATA SHEETCT49021N022.pdf/// LAGE RATING - DC28V// LAGE RATING - ACSolder, Quick Connect - 0.250° (6.3mm)// RUITATION STYLESolder, Quick Connect - 0.250° (6.3mm)SWITCH FUNCTIONOn-Off-OnSWITCH FUNCTIONGrouder - 12.20mm DiaSWITCH FUNCTIONGrouder - 12.20mm DiaSWITCH FUNCTIONGrouder - 12.20mm DiaSWITCH FUNCTIONGrouder - 0.250° (6.3mm)SWITCH FUNCTIONGrouder - 12.20mm DiaSWITCH FUNCTIONGrouder - 12.20mm DiaSWITCH FUNCTIONGrouder - 12.20mm DiaADD THER NAMESGrouder - 0.250° (6.3mm)ODITER NAMESGrouder - 0.250° (6.3mm)ADD THER NAMESGrouder - 0.250° (6.3mm)ADD THER NAMESGrouder - 0.250° (6.3mm)ADD THEN NAMESGrouder - 0.250° (6.3mm)ADD THER NAMESGrouder - 0.250° (6.3mm)ADD THEN NAMESGrouder - 0.250° (7.3mm)ADD THEN NAMESGrouder - 0.250° (7.3mm)ADD THEN NAMESGroud	PART NUMBER	CT49021N022
ADD FREE STATUS / ROHS STATUSLead free / RoHS CompliantQUANTITY AVAILABLE4115 pcsDATA SHEET© CT49021N022.pdf/OLTAGE RATING - DC28V/OLTAGE RATING - ACSolder, Quick Connect - 0.250° (6.3mm)/OLTAGE RATING - AC0n-Off-OnSWITCH FUNCTIONOn-Off-OnSWITCH FUNCTIONGrcular - 12.20mm DiaSWITCH FUNCTIONGrcular - 12.20mm DiaMOUNTING TYPEGrcular - 12.20mm DiaAUDUNTING TYPEGrcular - 12.20mm DiaMOUNTING TYPEGrcular - 12.20mm DiaMUNTING TYPEGrcular - 12.20mm DiaMUNTING TYPEGrcular - 12.20mm DiaMUNTING TYPEGrcular - 10.20mm DiaMUNTINATION VOLTAGE (NOMINAL)-CHUNINATION VOLTAGE (NOMINAL)-CHUNINATION VOLTAGE (NOMINAL)-CHUNINATION TYPE, COLORGrade - FullyCHUNINATION TYPE, COLOR10.000 CyclesCHUNINATION TYPEGrcular - 10.200 CyclesCHUNINATION TYPEGrcular - 10.200 CyclesCHUNINATION CHUNINALGrcular - 10.200 Cycles<	MANUFACTURER	APEM Inc.
QUANTITY AVAILABLE4115 pcsQUANTITY AVAILABLEGCT49021N022.pdfADATA SHEETGCT49021N022.pdfVOLTAGE RATING - DC28VVOLTAGE RATING - AC25VVOLTAGE RATING - ACOn-Off-OnSERIESCTADATA SHEET (UTOUT DIMENSIONSGroular - 1.2.20mm DiaADALE CUTOUT DIMENSIONSBulkCOLTAGE RATING TEMPERATURE679-3627ADAUTING TYPEPanel MountADOUNTING TYPEPanel MountADOUNTING TYPEInformationADOUNTING TYPEInformationADOUNTING TYPEInformationADOUNTING TYPEInformationADOUNTING TYPEInformationADOUNTING TYPEInformationADOUNTING TYPEInformationADOUNTING TYPEInformationADOUNTING TYPEInformationADOUNTING TYPEInformationADOUTING TYPEInformationADOUTING TYPEInformationILLUMINATION VOLTAGE (NOMINAL)InformationILLUMINATION TYPE, COLORInformationILLUMINATION TYPE, COLORInformationILLUMI	DESCRIPTION	SWITCH TOGGLE DPDT 10A 125V
DATA SHEETCT49021N022.pdfVOLTAGE RATING - DC28VVOLTAGE RATING - AC155VFERMINATION STYLESolder, Quick Connect - 0.250" (6.3mm)SWITCH FUNCTION0n-Off-OnSWITCH FUNCTIONCTSWITCH FUNCTIONCrular - 12.20mm DiaSWITCH FUNCTIONBulkACKAGINGBulkDTHER NAMES679-3627ADUNTING TYPEPanel MountADUNTING TYPEPanel MountADUNTING TYPEPanel MountADUNTING TYPEIdunited)NGRESS PROTECTIONIdunitedLLUMINATION VOLTAGE (NOMINAL)-LLUMINATION TYPE, COLORSaled - FullyLLUMINATION TYPE, COLORIdunitedCETCRICAL LIFE10,000 CyclesCETCRICAL LIFEIdunitationCURRENT RATINGIdunitationCURRENT RATINGIdunitation<	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
AQUITAGE RATING - DC28VAVOITAGE RATING - AC15VFERMINATION STYLESolder, Quick Connect - 0.250" (6.3mm)SWITCH FUNCTIONOn-Off-OnSWITCH FUNCTIONOn-Off-OnSWITCH FUNCTIONCroular - 12.20mm DiaSWITCH FUNCTIONBulkSPACKAGINGBulkDYPERATING TEMPERATURE679-3627ADUINTING TYPEPanel MountADUINTING TYPEAnaly (101mited)ADUINTING TYPEIcal free / RoHS CompliantADUINTING TYPE, COLORIcal free / RoHS CompliantADUINTING TYPE, COLORIcal free / RoHS CompliantADUINTING TYPE, COLORIcal free / RoHS CompliantADUINTATION YOPL, COLORIcal free / RoHS CompliantADUINTATIONIcal free	QUANTITY AVAILABLE	4115 pcs
YOLTAGE RATING - AC125VYOLTAGE RATING - ACSolder, Quick Connect - 0.250" (6.3mm)FERMINATION STYLEOn-Off-OnSWITCH FUNCTIONOn-Off-OnSWITCH FUNCTIONCroular - 12.20mm DiaSWITCH FUNCTIONGroular - 12.20mm DiaADUNTING TYPEHondADUNTING TYPEHondADUNTING TYPEIdentifiedADUNTING TYPEIdentifiedILLUMINATION VOLTAGE (NOMINAL)IdentifiedILLUMINATION TYPE, COLORIdentifiedALLUMINATION TYPE, COLORIdentifiedALLUMINATION TYPE, COLORIdentifiedILLUMINATION TYPE, COLORIdentifiedILLUMINATION TYPE, COLORIdentifiedILLUMINATION TYPE, COLORIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedILLUMINATIONIdentifiedIL	DATA SHEET	EFF CT49021N022.pdf
FERMINATION STYLESolder, Quick Connect - 0.250" (6.3mm)SWITCH FUNCTIONOn-Off-OnSWITCH FUNCTIONCTSWITCH FUNCTIONCIrcular - 1.2.0mm DiaSWITCH FUNCTIONSeriesAVAEL CUTOUT DIMENSIONSGroud - 1.2.0mm DiaSWITCH FUNCTIONSulkSPERATING TEMPERATURE69-3627OPERATING TEMPERATUREAnot C ~ 85°CAVOUNTING TYPEJone MountAVOUNTING TYPEIdentificationAVOUNTING TYPELead Free / ROHS COmpliantAND SERS PROTECTIONP67 - Dust Tight, WaterproofALLUMINATION VOLTAGE (NOMINAL)-ALLUMINATION TYPE, COLORJone / 1.2.ALLUMINATION TYPE, COLORSeled - FullyALLUMINATION TYPE, COLORJone / 1.2.ALLUMINATION TYPE, COLORJONE / 1.2.ALLUMINATIONJONE / 1.2.ALLUMINATIONJONE / 1.2.ALLUMINATIONJONE / 1.2.ALLUMINATIONJONE / 1.2.ALLUMINATIONJONE / 1.2.ALLUMINATIONJO	VOLTAGE RATING - DC	28V
SWITCH FUNCTION On-Off-On SERIES CT AVANEL CUTOUT DIMENSIONS CT CACKAGING CIRCUAR - 12.20mm Dia Bulk COTHER NAMES 679-3627 ACKAGING TEMPERATURE -40°C ~ 85°C ADDERATING TEMPERATURE -40°C ~ 85°C ADDERATING TEMPERATURE -40°C ~ 85°C ADDITING TYPE PARE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant ADJISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LILUMINATION VOLTAGE (NOMINAL) - LILUMINATION VOLTAGE (NOMINAL) - LILUMINATION TYPE, COLOR - CIRCUIT - 10,000 Cycles CIRCUIT - 10,000 Cycles CIR	VOLTAGE RATING - AC	125V
GRIESCTANEL CUTOUT DIMENSIONSCircular - 12.20mm DiaANCKAGINGBulkACKAGINGSP-3627DIFLER NAMESG79-3627OPERATING TEMPERATURE40°C ~ 85°CADUNTING TYPEPanel MountADISTURE SENSITIVITY LEVEL (MSL)I (Unlimited)ADISTURE SENSITIVITY LEVEL (MSL)I (Adi free / ROHS CompliantADISTURE SENSITIVITY LEVEL (MSL)IP67 - Dust Tight, WaterproofADISTURE SENSITIVITY DEVEL (MSL)IP67 - Dust Tight, WaterproofALUMINATION VOLTAGE (NOMINAL)IP61 - Dust Tight, WaterproofALUMINATION TYPE, COLORIP60 - Dust Tight, WaterproofADISTURE SENSITIVITY DEVELORIP60 - Dust Tight, WaterproofADISTURATIONIP61 - Dust Tight, WaterproofADISTURATIONIP61 - Dust Tight, WaterproofADISTURATIONIP60 - Dust Tight, WaterproofADISTURATIONIP61 - Dust Tight, WaterproofADISTURATIONIP61 - Dust Tight, WaterproofADISTURATIONIP61 - Dust Tight, WaterproofADISTURATIONIP61 - DUSTADISTURATIONIP61 - DUSTADISTURATIONIP61 - DUSTADISTURATIONIP61 - DUSTADISTURATIONIP61 - DUSTADIST	TERMINATION STYLE	Solder, Quick Connect - 0.250" (6.3mm)
ANEL CUTOUT DIMENSIONSCircular - 12.20mm DiaPARAEL CUTOUT DIMENSIONSFilcular - 12.20mm DiaPACKAGINGBulkPACKAGING679-3627POTHER NAMES-40°C ~ 85°CPOTHER TIME TEMPERATUREPanel MountPOUNTING TYPEPanel MountPOUNTING TYPELead free / RoHS CompliantPOINT SENSITIVITY LEVEL (MSL)Lead free / RoHS CompliantPOINT SENS PROTECTIONPOS - Dust Tight, WaterproofPLUMINATION VOLTAGE (NOMINAL)-PLUMINATION TYPE, COLORSeled - FullyPLUMINATION TYPE, COLOR10,000 CyclesPLUMINATION TYPE, COLORTogle Switch DPDT Panel MountPLUMINATIONPOTPLUMINATIONPOTPLUMINATIONDPDTPLUMINATIONSendard RoundPLUMINATIONSendard RoundPLUMINATIONPOTPLUMINATIONPOTPLUMINATIONSendard RoundPLUMINATIONSendard R	SWITCH FUNCTION	On-Off-On
AACKAGING Buk PACKAGING FUNCTIONAL PACKAGING P	SERIES	СТ
DTHER NAMES679-3627OPERATING TEMPERATURE-40°C ~ 85°CPOUNTING TYPEPanel MountMOUNTING TYPE1 (Unlimited)MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantNGRESS PROTECTION167 - Dust Tight, WaterproofLLUMINATION VOLTAGE (NOMINAL)-LLUMINATION TYPE, COLOR-LLUMINATION TYPE, COLORSealed - FullyELECTRICAL LIFE10,000 CyclesCURRENT RATINGNord CyclesCURRENT RATING104 (C), 154 (DC)CURRENT RATING1072CURRENT RATING1072CURTOT TYPE1532-32ACTUATOR TYPEStandard RoundACTUATOR TYPEKick Plated	PANEL CUTOUT DIMENSIONS	Circular - 12.20mm Dia
PERATING TEMPERATURE-40°C ~ 85°CPOUNTING TYPEPanel MountPOUNTING TYPE1 (Unlimited)PAGE STATUS / ROHS STATUSLead free / ROHS CompliantLEAD FREE STATUS / ROHS STATUSPfo7 - Dust Tight, WaterproofILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLORNon-IlluminatedILLUMINATION TYPE, COLORSealed - FullyILLUMINATION TYPE, COLOR10,000 CyclesIECTRICAL LIFE10,000 CyclesIECTRICAL LIFEIDA (AC), 15A (DC)ICLUQITPDTICLUATION TYPE, COLOR15/32-32ICLUATOR TYPEStandard RoundICLUATOR TYPEStandard Round	PACKAGING	Bulk
ACUNTING TYPEPanel MountMOUNTING TYPE1 (Unlimited)MOUNTING TYPE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION1P67 - Dust Tight, WaterproofILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-ILLUMINATION TYPE, COLORSeled - FullyEATURESSeled - FullyEATURES10,000 CyclesECTRICAL LIFE10,000 CyclesECTRICAL LIFEDEDTCURRENT RATINGDPTCURRENT RATING15/32-32ACTUATOR TYPESendard RoundACTUATOR TYPESendard RoundACTUATOR TYPESendard Round	OTHER NAMES	679-3627
ACUATOR SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS LEVEL (MSL) 2014 LEAD FREE STATUS / ROHS STATUS 1067 MGRESS PROTECTION 1070 MGRESS PROTECTION 1070 LUUMINATION VOLTAGE (NOMINAL)	OPERATING TEMPERATURE	-40°C ~ 85°C
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINGRESS PROTECTIONIP67 - Dust Tight, WaterproofILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLORNon-IlluminatedILLUMINATION TYPE, COLORSealed - FullyEATURESSealed - FullyEATURES10,000 CyclesILLUMINATIONToggle Switch DPDT Panel MountILLUMINATIONIntercompliantILLUMINATIONIntercompliantEATURESIntercompliantILLUMINATIONIntercompliant<	MOUNTING TYPE	Panel Mount
NGRESS PROTECTIONIP67 - Dust Tight, WaterproofLLUMINATION VOLTAGE (NOMINAL)-LLUMINATION TYPE, COLOR-LLUMINATIONNon-IlluminatedLLUMINATIONSealed - FullyEATURES10,000 CyclesELECTRICAL LIFE1000 CyclesCURRENT RATING104 CAC, 15A (DC)CURRENT RATINGDPDTCURRENT RATING15/32-32CURRENT RATION5/302 CyclesCURRENT RATING15/32-32CURRENT RATIONStandard RoundCURRENT RATION<	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
Clumination voltage (NOMINAL)-Clumination TYPE, COLOR-CluminatedNon-IlluminatedCluminatedSealed - FullyELECTRICAL LIFE10,000 CyclesCURRENT RATINGToggle Switch DPDT Panel MountCLURENT RATINGDPDTCLURENT RATING THREAD15/32-32ACTUATOR TYPEStandard RoundACTUATOR MATERIALNickel Plated	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
LLUMINATION TYPE, COLOR-LLUMINATIONNon-IlluminatedELEUTRICALSealed - FullyELECTRICAL LIFE10,000 CyclesDETAILED DESCRIPTIONToggle Switch DPDT Panel MountCURRENT RATINGDPDTCURRENT RATING15/32-32ACTUATOR TYPEStandard RoundACTUATOR MATERIALNickel Plated	INGRESS PROTECTION	IP67 - Dust Tight, Waterproof
LLUMINATIONNon-IlluminatedFEATURESSealed - FullyELECTRICAL LIFE10,000 CyclesDETAILED DESCRIPTIONToggle Switch DPDT Panel MountCURRENT RATING10A (AC), 15A (DC)CIRCUITDPDTBUSHING THREAD15/32-32ACTUATOR TYPEStandard RoundACTUATOR MATERIALNickel Plated	ILLUMINATION VOLTAGE (NOMINAL)	-
FEATURESSealed - FullyELECTRICAL LIFE10,000 CyclesDETAILED DESCRIPTIONTogle Switch DPDT Panel MountCURRENT RATING104 (AC), 15A (DC)CIRCUITDPDTBUSHING THREAD15/32-32ACTUATOR TYPEStandard RoundACTUATOR MATERIALNickel Plated	ILLUMINATION TYPE, COLOR	-
ELECTRICAL LIFE10,000 CyclesDETAILED DESCRIPTIONToggle Switch DPDT Panel MountCURRENT RATING10A (AC), 15A (DC)CIRCUITDPDTBUSHING THREAD15/32-32ACTUATOR TYPEStandard RoundACTUATOR MATERIALNicke Plated	ILLUMINATION	Non-Illuminated
DETAILED DESCRIPTIONToggle Switch DPDT Panel MountCURRENT RATING10A (AC), 15A (DC)CIRCUITDPDTBUSHING THREAD15/32-32ACTUATOR TYPEStandard RoundACTUATOR MATERIALNickel Plated	FEATURES	Sealed - Fully
CURRENT RATING10A (AC), 15A (DC)CIRCUITDPDTBUSHING THREAD15/32-32ACTUATOR TYPEStandard RoundACTUATOR MATERIALNickel Plated	ELECTRICAL LIFE	10,000 Cycles
CIRCUIT DPDT BUSHING THREAD 15/32-32 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Nickel Plated	DETAILED DESCRIPTION	Toggle Switch DPDT Panel Mount
BUSHING THREAD 15/32-32 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Nickel Plated	CURRENT RATING	10A (AC), 15A (DC)
ACTUATOR TYPE Standard Round	CIRCUIT	DPDT
ACTUATOR MATERIAL Nickel Plated	BUSHING THREAD	15/32-32
	ACTUATOR TYPE	Standard Round
ACTUATOR LENGTH 17.50mm	ACTUATOR MATERIAL	Nickel Plated
	ACTUATOR LENGTH	17.50mm

Related Tags

APEM Inc. CT49021N022	CT49021N022 Distributor	CT49021N022 Supplier
CT49021N022 Price	CT49021N022 Pictures	CT49021N022 Image
CT49021N022 PDF Datasheet	CT49021N022 Download Datasheet	CT49021N022 Datasheet
CT49021N022 Stock	Buy CT49021N022	Buy APEM Inc. CT49021N022
APEM Inc. CT49021N022	APEM Inc. Supplier	APEM Inc. Distributor
APEM Inc. CT49021N022	APEM Components, LLC CT49021N022	APEM Components, LLC CT49021N022

Related Products



CT49001N020

Manufacturers: APEM Inc. Description: SWITCH TOGGLE DPDT 10A 125V In stock: 4883 pcs



CT4C

Manufacturers: Dialight Description: LINKING CABLE 4WAY COMMON CONN In stock: 4618 pcs

RFQ



CT48BK175-L

RFQ

RFQ

Manufacturers: 3M Description: 48" BLACK 175LB CABLE TIE In stock: 37301 pcs



CT49021N000

Manufacturers: APEM Inc. Description: SWITCH TOGGLE DPDT 10A 125V In stock: 4294 pcs

RFQ



CT48NT175-L

Manufacturers: 3M Description: 48" NATURAL 175LB CABLE TIE In stock: 37027 pcs

RFQ



CT4MLXM

Manufacturers: Dialight Description: LINKING CABLE 4WAY-8WAY MALE In stock: 5149 pcs

RFQ



CT49021N002

Manufacturers: APEM Inc. Description: SWITCH TOGGLE DPDT 10A 125V In stock: 4312 pcs

RFQ

CT4BK18-C

Manufacturers: 3M Description: 4" BLACK 18LB CABLE TIE In stock: 396908 pcs

RFQ





Manufacturers: Dialight

Description: LINKING CABLE 4WAY-8WAY FEMALE In stock: 6039 pcs

RFQ



CT49001N000

Manufacturers: APEM Inc. Description: SWITCH TOGGLE DPDT 10A 125V In stock: 5252 pcs

RFQ

Copyright © 2020 Reliable Distributor of Electronic Components

E-mail: Info@infinity-electronic.com

Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong

