SDA03H0B Details PDF

product details.





SDA03H0B

Part Number:
Manufacturer/Brand:
Product description
Datasheets:
RoHs Status
Stock Condition
Ship From
Shipment Way

C&K SWITCH SLIDE DIP SPST 25MA 24V SDA03H0B.pdf Lead free / RoHS Compliant 87404 pcs stock Hong Kong DHL/Fedex/TNT/UPS/EMS

SDA03H0B

REQUEST FOR QUOTATION

Specifications of SDA03H0B

NANJEACTURERCKDESCRIPTIONSWITCH SLIDE DIP SPST ZSMA 24VLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantQUANTTY AVAILABLE2404 pseDATA SHEETSCA03408.pdfVOLTACE RATINGVS CVOLTACE RATINGVS CSTRENILINTION STYLESOASTRENILINTION STYLESOAPICHU002 (2.54mm), FullPICKAGINGSCA03408.pdfPICKAGINGSCA03408.pdfVOLTACE RATINGSOASTRENILINTION STYLESOAPICKAGINGSCA03408.pdfOTHER NAMESSCA03409.pdfOTHER NAMESSCA03408.pdfONGURTING THREA9C ~ SS°CNUMERE OF POSITIONS3MOURTING STYLEJOA (Sda MIDG)NOURTING THREJOA (Sda MIDG)MECHANICAL LIFEJOA (Sda MIDG)LIGTHJOA (Sda MIDG)LIGTHJOA (Sda MIDG)REGURTING THREJOA (Sda MIDG)REGURTING THREJOA (Sda MIDG)LIGTH ABOVE BOARDJOA (Sda MIDG)LIGTH ABOVE BOARDJOA (Sda MIDG)LIGTH ABOVE BOARDJOA (Sda MIDG)LIGTH CALLIFEJOB (Sda MIDG)LIGTH CALLIFEJOB (Sda MIDG)CITATE TINSHGAICITATE TINSHGAICINTACT FINSHGAICINTACT FINSHGAICINTACT FINSHSANGAICECINTACT FINSHShong MIDG)CINTACT FINSHShong MIDG)CINTACT FINSHShong MIDG)CINTACT TINSHShong MIDG)<		
DESCRIPTIONSWTCH SLIDE DIP SPST 25MA 24VLEAD FREE STATUS / ROHS STATUSEad free / ROHS CompliantQUANTIY AVAILABLESTA03H0R.pdfDATA SHEETSCA03H0R.pdfWISHABLEVICVILTAGE RATINGSVDCSERLESDATASERLESSDA03H0R.pdfPACAGINGSDA03H0R.pdfPACAGINGSDA03H0R.pdfPACAGINGSDA03H0R.pdfPACAGINGSDA03H0R.pdfPACAGINGSDA03H0R.pdfPACAGINGSDA03H0R.pdfPACAGINGSDA03H0R.pdfPACAGINGSDA03H0R.pdfOPERATING TEMPERATURESDA03H0R.pdfOPERATING TEMPERATURESDA03H0R.pdfOPERATING TEMPERATURESDA03H0R.pdfOUDUTION TYPESTA03H0R.pdfMUMERO FORDITIONS3MOUNTING TYPEInvolutiNed STATUSMUSTURE SERSTITUTY LEVEL (MSL)InvolutiNed STATUSRETARESSCA03H0R.pdfFEATURESSCA03H0R.pdfRETARESSCA03H0R.pdfRETARESSCA03H0R.pdfRETARESIndivide SCA0H0R.pdfRETARESSCA0H0R.pdfRETARESSCA0H0R.pdfRETARESSCA0H0R.pdfRETARESSCA0HOR.pdfRETARESSCA0HOR.pdfRETARESSCA0HOR.pdfRETARESSCA0HOR.pdfRETARESSCA0HOR.pdfRETARESSCA0HOR.pdfRETARESSCA0HOR.pdfRETARESSCA0HOR.pdfRETARESSCA0HOR.pdfRETARESSCA0HOR.pdfR	PART NUMBER	SDA03H0B
LEAD FREE STATUS / ROMS STATUSLead free / RoHS CompliantQUANTTY AVALABLE850A03H08.pdfDATA SHEETYsWASHABLEYsVOLTAGE RATING9VDCSERLISSAPTCH0.00° (2.5Hm), FullSARGANGTubePACKAGING- SAN03H08.pdfOTHER MARESSAN03H08.pdfOTHER MARES- SAN03H08OTHER MARES- SAN03H08NOUTING TYPE- SAN03H08NOUTING TYPE- SAN03H08LEAD RESE STATUS / ROHS STATUS- Lead free / ROHS CompliantLEAD RESE STATUS / ROHS STATUS- SAN03H08LEAD RESE STATUS / RO	MANUFACTURER	C&K
QUANTITY AVAILABLER04 PageDATA SHEETR0503H08.pdfX05AFABLEYesVILTAGE RATINGPVPCYOLTAGE RATINGR0 PinSERLESSDAPTCH0.10° (2.54mm), FullPCAGGINGTobOTHER NAMESSOBO3H08.pdfOTHER NAMES40°C ~ 8°COTHER NAMES40°C ~ 8°CNUMEER OF POSITIONS3MOUNTING TYPE1000 CyclesMOUNTING TYPE(Julimited)MOUNTING TYPE0.30° (Schom)MEER STATUS / ROHS STATUS1000 CyclesEIGT ABOVE BOARD1.30° (Schom)EIGT ABOVE BOARD1.30° (Schom)EIGT ABOVE BOARD1.30° (Schom)EIGT RATUS / ROHS STATUS0.30° (Schom)EIGT RATUS / ROHS STATUS1.30° (Schom)CITATCT RATUS1.30° (Schom)	DESCRIPTION	SWITCH SLIDE DIP SPST 25MA 24V
Data sheatSb03408.pdfWASHABLEYosVOLTAGE PATING24VCVOLTAGE PATINGCP InSERIESSDAPTCH0100° (2.54mm), FullPACKAGINGTubeOTHER NAMESSDAOTHER NAMESSDANUMBER OF POSITIONSSMOUNTING TYPEInformationMOUNTING TYPEInformationMOUNTING TYPESTAMOUNTING TYPESTAMOUNTING TYPEInformationMOUNTING TYPEInformationMOUNTING TYPEInformationIELEG TALLE DESCRIPTIONSDADIFALLED DESCRIPTIONSDACONTACT FINISHGACONTACT FINISHGACONTACT FINISHGACONTACT FINISHSDACONTACT FINISHSDACONTACT FINISHSDACONTACT FINISHSDACONTACT FINISHSDACONTACT FINISHSDACONTACT FINISH <td< td=""><td>LEAD FREE STATUS / ROHS STATUS</td><td>Lead free / RoHS Compliant</td></td<>	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
wskrake ws wskrake ws wskrake ws volrade rating 240C treknivation style DP in series Sol prick 100° (2.54m), Full prick Sol prick Sol orter Sol	QUANTITY AVAILABLE	87404 pcs
VOLTAGE RATING24VDCTERNINATION STYLECP IRSERIESSDAPTCH0.0° (2.54mm), FullPACKAGINGTuBortHER NAMESSANO3H08OPERATING TEMPERATURE40° C ASCOOPERATING TEMPERATURE40° C ASCONUMEER OF POSITIONS40° C ASCOMOUNTING TYPETuogi HuleMOUNTING TYPE1000 CyclesLENGTH0.002 CyclesLENGTH0.015 CyclesCYCLES0.015 CyclesLENGTH0.015 CyclesCYCLES0.015 CyclesCYCLES0.015 CyclesCYCLES0.015 CyclesCYCLES0.015 CyclesCYCLES0.015 CyclesCYCLES0.015 CyclesCYCLES0.015 CyclesCYCLES0.015 CyclesCYCLE	DATA SHEET	DE SDA03H0B.pdf
TRRINATION STYLEPC PinSRIPSSOAPTCH0.00° (2.54m), FullPACKAGINGTOEOTHER NAMESSDAD3M0SOTHER NAMES.00° (2.54m), FullOTHER NAMES.00° (2.54m), FullOTHER NAMES.00° (2.54m), FullNUMERE OF POSITIONS.0° (2.5%)MOUTING TYPE.0° (2.6%)MOUTING TYPE.0° (2.6%)MOUTING SITURY LAVEL (MSL).0° (2.6%)MIGHANICAL LIFE.0° (2.6%)LENDA.0° (2.6%)CONTACT HATENAL.0° (2.6%)	WASHABLE	Yes
SRIESSDAPITH.00°(2.54m), FullPACAGINGNoPACAGINGSAQA3H0GOTHER NAMESSAQA3H0GOPERATING TEMPERATURE.06°(ASSC)NUMERO POSITIONS3MOUTING TYPEMONGNAGCMOUTING TYPE.0100 (ASGC)MOSTORE SENSITIVIT VLEVL (MSL).0100 (ASGC)MIGHANICAL LIFE.0200 (ASGC)LIGATA ALE SEASAND.0100 (ASGC)LIGATA RADOKE BOARD.0376 (ASGC)HEIGHT ABOVE BOARD.0300 (ASGC)ELGERICAL LIFE.0000 (ASGC)LIGATERATURE.0000 (ASGC)LIGATA ALE SEASAND.0000 (ASGC)LIGATERATURE.0000 (ASGC)CIARENT RATURG.0000 (ASGC)CONTACT MATERIAL.0000 (ASGC)CONTACT FINISH.04100 (ASGC)CONTACT FINISH.04100 (ASGC)CONTACT FINISH.041000 (ASGC)CONTACT FINISH.04000 (ASGC)CONTACT FINISH.04000 (ASGC)CONTACTELIAL.04000 (ASGC)CONTACTELIAL.04000 (ASGC)CONTACTELIAL.04000 (ASGC)CONTACTELIAL.04000 (ASGC)CONTACTELIAL.04000 (ASGC)CONTACTELIAL.040000 (ASGC)CONTACTELIAL.040000 (ASGC)CONTACTELIAL.0400000 (ASGC)CONTACTELIAL.0400000 (ASGC)CONTACTELIAL.04000000 (ASGC)CONTACTELIAL.0400000000 (ASGC)CONTACTELIAL.0400000000000000000000000000000000000	VOLTAGE RATING	24VDC
Pitch0.000 (2.54m), FullPACKAGINGVacPACKAGINGVacother NAMES- 800-301000other NAMES- 800-20000OTERATING TEMPERATURE- 800-20000NUBER OF POSITIONS- 800-20000MOUNTING TYPE- 1000000000000000000000000000000000000	TERMINATION STYLE	PC Pin
PACKAGINGTubeOTHER NAMESSSA03H0B SSA03H0B SSA03H0BOTHER NAMES-40C~ ASCOPERATING TEMPERATURE-40C~ ASCNUMBER OF POSITIONS3MOUNTING TYPETongh HoleMOUNTING TYPE(10/Imited)MOSTURE SENSITIVITY LEVEL (MSL)(10/Imited)MECHANICAL LIFE(10/Imited)LENGTH(10/Imited)LENGTH(10/Imited)LENGTH(10/Imited)LENGTH ABOVE BOARD(10/Imited)HEIGHT ABOVE BOARD(10/Imited)ELECTRICAL LIFE(10/Imited)LECTRICAL LIFE(10/Imited)PATURES(10/Imited)ELECTRICAL LIFE(10/Imited)DETALED DESCRIPTION(10/Imited)CURRENT RATING(10/Imited)CURRENT RATING(10/Imited)CURRENT RATING(10/Imited)CONTACT HINISH(10/Imited)CONTACT FINISH(10/Imited)CONTACT FINISH(10/Imited)	SERIES	SDA
orter NAMESSpANatherorter Attive EMPERATURE-40° ~ 85°CNUMBER OF POSITIONS3MOUTING TYPEInval HoleMOSTURE SENSTITUTY LEVEL (MSL)100 CyclesMECHANICAL LIFE0.00 CyclesLENGTH0.00 CyclesLENGTH CALOR STATUS0.01 CyclesHEIGHT ABOVE BOARD100 CyclesELERTICAL LIFE0.02 CyclesLEIGTICAL LIFE0.02 CyclesLEIGTICAL LIFE0.02 CyclesELERTICAL LIFE0.02 CyclesELERTICAL LIFE0.02 CyclesELERTICAL LIFE0.02 CyclesCURRENT TATING0.02 CyclesCURRENT TATING0.02 CyclesCURRENT TATING0.02 CyclesCURRENT TATING0.02 CyclesCURRENT FAITING0.02 CyclesCURRENT FAITING0.02 CyclesCURRENT FAITING0.02 CyclesCONTACT FINISH0.02 Cycles	PITCH	0.100" (2.54mm), Full
OTHER NAMESCKN6057OPERATING TEMPERATURE40°C ~ 85°CNUMBER OF POSITIONS3MOUNTING TYPETrough HoleMOINTING TYPE(Unlinited)MECHANICAL LIFE0.000 CyclesLENGTH0.007 CyclesLEAD FREE STATUS / ROHS STATUSCad Free / ROHS CompliantFEGHT ABOVE BOARD1.000 CyclesELECTRICAL LIFE0.000 CyclesELECTRICAL LIFE1.000 CyclesELECTRICAL LIFE0.000 CyclesELECTRICAL LIFE0.000 CyclesELECTRICAL LIFE0.000 CyclesCONTACT MATERIALSmAllCONTACT FINISHGoldCONTACT FINISHGoldCONTACT FINISHSmSBODY MATERIALSpSInder (Stendard) Actuator 25m A2400CBODY MATERIALSide (Standard)CATLATOR TYPESide (Standard)	PACKAGING	Tube
NUMBER OF POSITIONS3MOUNTING TYPEFrough HoleMOUNTING TYPEInfond HoleMOSTURE SENSITIVIT LEVEL (MSL)InfondMECHANICAL LIFEJ00 CqeBLENGTHG376 (GompilatLENGTRE STATUS / ROHS STATUSInfor AGM SCH (MSL)HEGH TABOVE BOARDIS87 (AGSM)ELETRICAL LIFEJ00 CqeBELETRICAL LIFEJ00 CqeBELETRICAL LIFEInfonder SCH (MSL)CURRENT RATINGSMC SCH (MSL)CURRENT RATINGSMC)CURRENT RATINGGMCCONTACT FINISHGICONTACT FINISHSMEBODY MATERIALSPIENERGENERGACTUATOR TYPESME (SCH GMC)	OTHER NAMES	
MOUNTING TYPEHough HoleMOUNTING TYPEI(Unimited)MOISTURE SENSITIVITY LEVEL (MSL)I(Unimited)MECHANICAL LIFEJ000 QdesLENGTH0.378" (9.0mm)LENGTHCad free / RoHS CompliantHEIGHT ABOVE BOARD108" (4.5mm)FATURESJ000 QdesELECTRICAL LIFEJ000 QdesELECTRICAL LIFEJ000 QdesELECTRICAL LIFEJ000 QdesCURRENT RATINGDis Wich SPS 14 Soltion Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATINGSimonCONTACT MATERIALGoldCONTACT FINISHGidCONTACT FINISHSimonCONTACT MATERIALSimonBODY MATERIALSimonACTUATOR TYPESimonSi	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimed) 1000 Cycles 100	NUMBER OF POSITIONS	3
MECHANICAL LIFE1,000 CyclesLENGTH0.378" (9.60mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.183" (4.65mm)FEATURESTape SealELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATINGSmACONTACT MATERIALGoldCONTACT FINISHGoldCONTACT FINISHSPSTBODY MATERIALPilyphenylene Sulfide (PPS)BODY MATERIALSide (Standard)BODY MATERIALSide (Standard)BODY MATERIALSide (Standard)	MOUNTING TYPE	Through Hole
LindControlLENGTH0.378° (0.60mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.183° (4.65mm)FATURESTape SealELECTRICAL LIFE0.00 CyclesDETAILED DESCRIPTIONDis Witch SPST 3 Position Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATINGSmACONTACT MATERIALGoldCONTACT FINISHGoldCONTACT STATUSSPSTBODY MATERIALMolyneyselfide (PSS)BODY MATERIALSide (Standard)BODY MATERIAL	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.183" (4.65mm)FEATURESTape SealELCTRICAL LIFE0.00 CyclesDETAILED DESCRIPTIONDis Wich SPST J Position Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATINGSmallCONTACT MATERIALGoldCONTACT FINISHGoldBODY MATERIALPippingen Sulfide (PSPS)BODY MATERIALSile (Standard)BODY MATERIALSile (Standard)	MECHANICAL LIFE	1,000 Cycles
HEIGHT ABOVE BOARDI.83" (4.65mm)FEATURESTap SalELCTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDis Witch SPST 3 Position Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATINGSmACONTACT FINISHGoldCINTACT FINISHSpSTBODY MATERIALPolypengengengengengengengengengengengengenge	LENGTH	0.378" (9.60mm)
FEATURESTape SealELECTRICAL LIFEJ,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATINGSmACONTACT MATERIALBeryllium CopperCONTACT FINISHGldCRCUTTSPSTBODY MATERIALPolyhenylen Sulfide (PPS)ACTUATOR TYPEBid (Standard)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE1,00 CyclesDETAILED DESCRIPTIONDip Switch SPG Storight Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATING25mACONTACT MATERIALBeylium CopperCONTACT FINISHGoldCIRCUITSP5BODY MATERIALPiphenseling (Standard)ACTUATOR TYPESite (Standard)	HEIGHT ABOVE BOARD	0.183" (4.65mm)
DETAILED DESCRIPTIONDip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATING25mACONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolypenselfiele (PPS)ACTUATOR TYPESide (Standard)	FEATURES	Tape Seal
CURRENT RATING25mACONTACT MATERIALBerylium CopperCONTACT FINISHGoldCIRCUITSP5TBODY MATERIALPolyhenyleng Sufide (PPS)ACTUATOR TYPESide (Standard)	ELECTRICAL LIFE	1,000 Cycles
CONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolypeng Sulfide (PPS)ACTUATOR TYPESile (Standard)	DETAILED DESCRIPTION	Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 25mA 24VDC
CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS) ACTUATOR TYPE Side (Standard)	CURRENT RATING	25mA
CIRCUITSPSTBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPESide (Standard)	CONTACT MATERIAL	Beryllium Copper
BODY MATERIAL Polyphenylene Sulfide (PPS) ACTUATOR TYPE Slide (Standard)	CONTACT FINISH	Gold
ACTUATOR TYPE Slide (Standard)	CIRCUIT	SPST
	BODY MATERIAL	Polyphenylene Sulfide (PPS)
ACTUATOR LEVEL Flush, Recessed	ACTUATOR TYPE	Slide (Standard)
	ACTUATOR LEVEL	Flush, Recessed

Related Tags

C&K SDA03H0B	SDA03H0B Distributor	SDA03H0B Supplier
SDA03H0B Price	SDA03H0B Pictures	SDA03H0B Image
SDA03H0B PDF Datasheet	SDA03H0B Download Datasheet	SDA03H0B Datasheet
SDA03H0B Stock	Buy SDA03H0B	Buy C&K SDA03H0B
C&K SDA03H0B	C&K Supplier	C&K Distributor
C&K SDA03H0B	C&K Components SDA03H0B	

Related Products



SDA03H0K

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 5612 pcs

RFQ



SDA03H0SBR

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 82736 pcs

RFQ



SDA02H1BD

SDA02H0SK

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 94014 pcs

RFQ



SDA03H0BD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 90540 pcs

RFQ



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 6914 pcs



SDA02H1SBD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 71894 pcs

RFQ

SDA03H0SB

SDA02H1SKD



SDA03H0SBD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 59779 pcs

RFQ

RFQ

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 48105 pcs

RFQ

SDA02H0SKD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 5472 pcs

RFQ

SDA03H0KD



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 3309 pcs

RFQ

C&K

C&K

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 5204 pcs

RFQ

SDA02H1KD



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 6111 pcs

RFQ

Copyright © 2020 Reliable Distributor of Electronic Components

E-mail: Info@infinity-electronic.com

Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong

