Grayhill



Grayhill, Inc.

71MB30-02-4-02N

Part Number:

Manufacturer/Brand: Product description

RoHs Status Stock Condition

Ship From Shipment Way

Datasheets:

71MB30-02-4-02N

Grayhill, Inc. SWITCH ROTARY

RoHS Compliant

3073 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER 71MB30-02-4-02N MANUACTURER Grayhil, Inc. DESCRIPTION SWITCH ROTARY LEAD FREE STATUS / ROHS STATUS ROHS Compilant QUANTITY ANALIABLE 3073 pcs DATA SHEET VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 71 ROHS Compilant ROHS STATUS ROHS COMPILANT RO		Specifications of 71MB30-02-4-02N
MANUFACTURER Grayhill, Inc. DESCRIPTION SWITCH ROTARY LEAD FREE STATUS / ROHS STATUS RoHS Compliant QUANTITY AVAILABLE 3073 pcs DATA SHEET VOLTAGE RATING - DC VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 71 ROHS STATUS ROHS Compliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 27.97mm CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Silver Alloy CONTACT FINSH - CIRCUIT PER DECK 4PDT A		
DESCRIPTION SWITCH ROTARY LEAD FREE STATUS / ROHS STATUS RoHS Compliant QUANTITY AVAILABLE 3073 pcs DATA SHEET VOLTAGE RATING - DC VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 71 ROHS Compliant PANEL CUTOUT DIMENSIONS - OPFRATTING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mounk INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 27.87mm CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE	PART NUMBER	71MB30-02-4-02N
LEAD FREE STATUS / ROHS STATUS RoHS Compliant QUANTITY AVAILABLE 3073 pcs DATA SHEET	MANUFACTURER	Grayhill, Inc.
QUANTITY AVAILABLE DATA SHEET VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 71 ROHS STATUS ROHS COMPILIAN PANEL CUTOUT DIMENSIONS - OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROLDER SCRIPTION ROLDER	DESCRIPTION	SWITCH ROTARY
DATA SHEET VOLTAGE RATING - DC VOLTAGE RATING - AC I15V TERMINATION STYLE Solder Lug SERIES 71 ROHS STATUS ROHS COMPliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTAGY SWItch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 2.7.87mm CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL SIEVE AIRON ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	LEAD FREE STATUS / ROHS STATUS	RoHS Compliant
VOLTAGE RATING - DC VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 71 ROHS STATUS ROHS COMPliant PANEL CUTOUT DIMENSIONS OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POSITIONS 2 NUMBER OF DECKS MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTON ROTON SOND AC/DC) CURRENT RATING CONTACT TIMING NOn-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	QUANTITY AVAILABLE	3073 pcs
TEMINATION STYLE Solder Lug SERIES 71 ROHS STATUS ROHS COMPliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTATION ROTATION ROTATION CURRENT RATING CONTACT TIMING CONTACT MATERIAL CONTACT MATERIAL CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° Flatted (6.35mm Dia)	DATA SHEET	
TERMINATION STYLE SERIES 71 ROHS STATUS ROHS Compliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTARY Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 2.7.87mm CURRENT RATING CONTACT TIMING NOn-Shorting (BBM) CONTACT TIMING CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	VOLTAGE RATING - DC	30V
ROHS STATUS ROHS COMPILIANT PANEL CUTOUT DIMENSIONS - OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROBARY SWItch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING NON-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	VOLTAGE RATING - AC	115V
ROHS STATUS ROHS Compliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 27.87mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° Flatted (6.35mm Dia)	TERMINATION STYLE	Solder Lug
PANEL CUTOUT DIMENSIONS - OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING NON-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	SERIES	71
OPERATING FORCE NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTARY Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 27.87mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	ROHS STATUS	RoHS Compliant
NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 27.87mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	PANEL CUTOUT DIMENSIONS	-
NUMBER OF POLES PER DECK NUMBER OF POLES PER DECK 2 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT TIMISH - CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	OPERATING FORCE	2.880 ~ 23gfm
NUMBER OF DECKS MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Panel Mount - Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm 27.87mm 250mA (AC/DC) 50mA (AC/DC) 40m-Shorting (BBM) CONTACT FINISH - Flatted (6.35mm Dia)	NUMBER OF POSITIONS	2
MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 27.87mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	NUMBER OF POLES PER DECK	4
INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 27.87mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° Flatted (6.35mm Dia)	NUMBER OF DECKS	2
FEATURES DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE ACTUATOR TYPE Flatted (6.35mm Dia)	MOUNTING TYPE	Panel Mount
DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm 27.87mm 25.0mA (AC/DC) 115VAC Panel Mount 27.87mm 25.0mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm 25.0mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount 27.87mm ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount ACTUATOR TYPE Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount ACTUATOR TYPE ACTUATOR	INDEX STOPS	Fixed
DEPTH BEHIND PANEL CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE 27.87mm ACTUATOR TYPE 27.87mm ACTUATOR TYPE 27.87mm ACTUATOR MATERIAL 27.87mm 4PDT ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	FEATURES	-
CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE 250mA (AC/DC) Non-Shorting (BBM) Silver Alloy 4PDT 4PDT ACTUATOR TYPE Flatted (6.35mm Dia)	DETAILED DESCRIPTION	Rotary Switch 2 Position 4PDT 250mA (AC/DC) 115VAC Panel Mount
CONTACT TIMING CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Non-Shorting (BBM) Silver Alloy - 4PDT 4PDT ACTUATOR TYPE Flatted (6.35mm Dia)	DEPTH BEHIND PANEL	27.87mm
CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Silver Alloy 4PDT 30° Flatted (6.35mm Dia)	CURRENT RATING	250mA (AC/DC)
CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE 4PDT 30° Flatted (6.35mm Dia)	CONTACT MATERIAL	Silver Alloy
ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT FINISH	-
ACTUATOR TYPE Flatted (6.35mm Dia)	CIRCUIT PER DECK	4PDT
	ANGLE OF THROW	30°
ACTUATOR LENGTH 9.53mm	ACTUATOR TYPE	Flatted (6.35mm Dia)
	ACTUATOR LENGTH	9.53mm

Related Tags

Grayhill, Inc. 71MB30-02-4-02N	71MB30-02-4-02N Distributor	71MB30-02-4-02N Supplier
71MB30-02-4-02N Price	71MB30-02-4-02N Pictures	71MB30-02-4-02N Image
71MB30-02-4-02N PDF Datasheet	71MB30-02-4-02N Download Datasheet	71MB30-02-4-02N Datasheet
71MB30-02-4-02N Stock	Buy 71MB30-02-4-02N	Buy Grayhill, Inc. 71MB30-02-4-02N
Grayhill, Inc. 71MB30-02-4-02N	Grayhill, Inc. Supplier	Grayhill, Inc. Distributor
Grayhill, Inc. 71MB30-02-4-02N	Grayhill Inc. 71MB30-02-4-02N	

Related Products



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY In stock: 3312 pcs

RFQ

71MB30-03-1-04N



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY In stock: 3785 pcs

71MB30-02-3-04N

RFQ



71MB30-02-3-03N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY In stock: 3350 pcs

RFQ



71MB30-02-6-02N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY In stock: 3139 pcs

RFQ



71MB30-02-5-02N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY In stock: 3029 pcs

RFQ

71MB30-02-2-04N



71MB30-02-1-10S Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY In stock: 4725 pcs RFQ



Description: SWITCH ROTARY In stock: 4108 pcs

RFQ



71MB30-02-2-05N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY In stock: 4016 pcs

RFQ



71MB30-02-4-03N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY In stock: 2934 pcs **RFQ**



71MB30-03-1-06N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY In stock: 3674 pcs **RFQ**



71MB30-02-2-05S



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY

71MB30-02B12N

In stock: 4518 pcs **RFQ**



Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY In stock: 4656 pcs **RFQ**















