Grayhill



Grayhill, Inc.

44M60-01-1-03N

Part Number: Manufacturer/Brand:

Product description Datasheets: RoHs Status Stock Condition

Ship From Shipment Way 44M60-01-1-03N

Grayhill, Inc.

SWITCH ROTARY 3POS 5A 115V

44M60-01-1-03N.pdf Lead free / RoHS Compliant

1941 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

PART NUMBER         44460 0.1-1.03N           MANUFACTURER         Grayhill, Inc.           DESCRIPTION         SWITCH ROTARY 3POS SA 115V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compilant           QUANTITY XAVILABUE         1941 DS           DATA SHEET         \$24460-01-1-03N.pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         115V           TERMINATION STYLE         Solder Lug           SERIES         44           PANEL CUTOUT DIMENSIONS         -           OFFER TAMES         Q548403S           OFFER TAMES         Q548403S           OFFER TAMES OF POSITIONS         3           NUMBER OF POSITIONS         3           NUMBER OF POSITIONS         1           MUMBER OF DECKS         1           MUMINITY OF PER DECK         1           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compilant           INDEX STOPS         Fixed           FEATURES         1           DETAILLED DESCRIPTION         Rodary Switch 3 Position SP3T SA (AC), 1A (DC) 115VAC Panel Mount           CUPETH BEHIND PANEL         SA (AC), 1A (DC)           CUNTACT TIMIN		Specifications of 44M60-01-1-03N
MANUFACTURER         Grayhil, Inc.           DESCRIPTION         SWITCH ROTARY 3POS SA 115V           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Campliant           QUARTITY AVAILABLE         1941 pcs           DATA SHEET         \$144160-01-1-03N.pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         115V           SERLES         44           PARLE CUTOUT DIMENSIONS         4           OTHER NAMES         QS48035           OPERATING FORCE         5.761 ~ 83fm           NUMBER OF POSITIONS         3           NUMBER OF POSITIONS         1           NUMBER OF DECK         1           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           INDEX STOPS         Fixed           FEATURES         2 (404mm           CURRENT RATING         ROALY SWIRCH 3 POSITION SPAT SA (AC), 1A (DC) 115VAC Panel Mount           DEPTH BELIND PANEL         3 (AC), 1A (DC)           CURRENT RATING         6 (AC), 1A (DC)           CURRENT RATING         5 (AC), 1A (DC)           CUNTACT TRITISH         6 (AC)           CUNTA		
DESCRIPTION         SWITCH ROTARY 3POS \$A 115V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         1941 pcs           DATA SHEET         ★ 14460-01-1-03N.pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         115V           TERNIANTION STYLE         Solder Lug           SERIES         44           PANEL CUTOUT DIMENSIONS         25484035           OTHER NAMES         Q5484035           OVERATING FORCE         5.761 ~ 83fm           NUMBER OF POSITIONS         3           NUMBER OF POSITIONS         3           NUMBER OF POSITIONS         1           MOUNTING TYPE         Panel Mount           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Rod free / RoHS Compliant           INDEX STOPS         Fixed           DETAILED DESCRIPTION         Rotary Switch 3 Position SP3T SA (AC), 1A (DC) 115VAC Panel Mount           CEPTH BEHIND PANEL         SA (AC), 1A (DC)           CONTACT TIMING         A (AC), 1A (DC)           CONTACT TIMING         SINVER Alloy           CONTACT FINISH         SINVER Alloy	PART NUMBER	44M60-01-1-03N
LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           QUANTITY AVAILABLE         1941 pcs           DATA SHEET         24460-01-103N.pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         115V           TERRIHATION STYLE         Solder Lug           SERIES         44           PARLE LOTTOUT DIMENSIONS         -           OTHER NAMES         Q548403S           OPERATING FORCE         5.761 ~ 83gfm           NUMBER OF POSITIONS         3           NUMBER OF DOSITIONS         1           MOUNTING TYPE         Panel Mount           MOUNTING TYPE         Panel Mount           MOUNTING TYPE         Panel Mount           MOSTURE SENSITIVITY LEVEL (MSL)         1 (Vnlimbed)           LEAD FREE STATUS / ROHS STATUS         Roder / ROHS Compliant           INDEX STOPS         Fixed           FEATURES         SCALLA (MC)           DETHALLED DESCRIPTION         Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount           DETHALLED DESCRIPTION         ACA, 1A (DC)           CUNTACT TRINIS         SOShorting (BBM)           CONTACT TRINIS         SOShorting (BBM)           CONTACT FINISH         SOShorting (BBM) <t< td=""><td>MANUFACTURER</td><td>Grayhill, Inc.</td></t<>	MANUFACTURER	Grayhill, Inc.
QUANTITY AVAILABLE         1941 pes           DATA SHEET         244460-01-1-03N.pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         115V           TERMINATION STYLE         Soler Lug           SERIES         44           PANEL CUTOUT DIMENSIONS         -           OFFER TIMES         Q548403S           OPERATING FORCE         5.761 ~ 83g/m           NUMBER OF POSITIONS         3           NUMBER OF POLES PRE DECK         1           NUMBER OF DECKS         1           MOUNTING TYPE         Panel Mount           MOISTURE SENSITUYITY LEVEL (MSL)         1 (Unlimited)           MIDEX STORS         1 (Unlimited)           TEATURES         1 (VOLTAGE STATUS / ROHS STATUS           TEATURES         2 (VOLTAGE STATUS / ROHS STATUS	DESCRIPTION	SWITCH ROTARY 3POS 5A 115V
DATA SHEET         € 44460-01-1-03N.pdf           VOLTAGE RATING - DC         25V           VOLTAGE RATING - AC         115V           TERMINATION STYLE         Solder Lug           SERIES         44           PANEL CUTOUT DIMENSIONS         -           OFFER TIMES         Q548403S           OPERATING FORCE         5.761 ~ 83gm           NUMBER OF POSITIONS         3           NUMBER OF POLES PER DECK         1           NUMBER OF DECKS         1           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RHS Compliant           INDEX STOPS         Fixed           FEATURES         Fixed           DETH BEHIND PANEL         25.04mm           CURRENT RATING         SA (AC), 1A (DC)           CONTACT TIMING         Non-Shorting (BBM)           CONTACT TIMING         SIVER Alloy           CONTACT FINISH         -           CRUIT PER DECK         SP3T           ANGLE OF THROW         60°           ANGLE OF THROW         Flatted (6.35mm Dia)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         155V           TERMINATION STYLE         Solder Lug           SERIES         44           PANEL CUTOUT DIMENSIONS         -           OTHER NAMES         Q5484035           OPERATING FORCE         5.76f ~ 83gfm           NUMBER OF POSITIONS         3           NUMBER OF POLES PER DECK         1           NUMBER OF DECKS         1           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           INDEX STOPS         Fixed           FEATURES         SOLATHAN SOLATION           DEPTH BEHIND PANEL         26.04mm           CURRENT RATING         SA (AC), 1A (DC)           CONTACT TIMING         Non-Shorting (BBM)           CONTACT TIMING         Silver Alloy           CONTACT FINISH         SP3T           ANGLE OF THROW         60°           ANGLE OF THROW         Fatted (6.35mm Dia)	QUANTITY AVAILABLE	1941 pcs
VOLTAGE RATING - AC         115V           TERMINATION STYLE         Solder Lug           SERIES         44           PANEL CUTOUT DIMENSIONS         -           OTHER NAMES         QS484035           OPERATING FORCE         5.761 ~ 83gfm           NUMBER OF POSITIONS         3           NUMBER OF POLES PER DECK         1           MOUNTING TYPE         Panel Mount           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           IEAD FREE STATUS / ROHS STATUS         Faxed           FEATURES         Fixed           PETATLES DESCRIPTION         Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount           DEPTH BEHIND PANEL         26.04mm           CURRENT RATING         Non-Shorting (BBM)           CONTACT TIMING         Non-Shorting (BBM)           CONTACT FINISH         -           CONTACT FINISH         Silver Alloy           CONTACT FINISH         60°           CHAUGH (5.35mm Dia)         Flattled (6.35mm Dia)	DATA SHEET	44M60-01-1-03N.pdf
TERMINATION STYLE         Solder Lug           SERIES         44           PANEL CUTOUT DIMENSIONS         -           OTHER NAMES         QS484035           OPERATING FORCE         5.761 ~ 83gfm           NUMBER OF POSITIONS         3           NUMBER OF POLES PER DECK         1           NUMBER OF DECKS         1           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Exed Free / RHS Compliant           INDEX STOPS         Fixed           FEATURES         Fixed           DETAILED DESCRIPTION         Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount           DEPTH BEHIND PANEL         26.04mm           CURRENT RATING         ACAC), 1A (DC)           CONTACT TIMING         Non-Shorting (BBM)           CONTACT MATERIAL         Silver Alloy           CONTACT FINISH         -           CICKLUT PER DECK         SP3T           ANGLE OF THROW         Filted (6.35mm Dia)	VOLTAGE RATING - DC	28V
SERIES         44           PANEL CUTOUT DIMENSIONS         -           OTHER NAMES         Q5484035           OPERATING FORCE         5.761 ~ 83gfm           NUMBER OF POSITIONS         3           NUMBER OF POLES PER DECK         1           NUMBER OF DECKS         1           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           INDEX STOPS         Fixed           FEATURES         Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount           DETAILED DESCRIPTION         Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount           CURRENT RATING         SA (AC), 1A (DC)           CONTACT TIMING         Non-Forting (BBM)           CONTACT MATERIAL         Silver Alloy           CONTACT FINISH         -           CICKUIT PER DECK         SP3T           ANGLE OF THROW         Folice (6.35mm Dia)	VOLTAGE RATING - AC	115V
PANEL CUTOUT DIMENSIONS         -           OTHER NAMES         Q5484035           OPERATING FORCE         5.761 ~ 839fm           NUMBER OF POSITIONS         3           NUMBER OF POLES PER DECK         1           NUMBER OF DECKS         1           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           INDEX STOPS         Fixed           FEATURES         -           DETAILED DESCRIPTION         Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount           DEPTH BEHIND PANEL         26.04mm           CURRENT RATING         5A (AC), 1A (DC)           CONTACT TIMING         Non-Shorting (BBM)           CONTACT FINISH         5Iver Alloy           CONTACT FINISH         5P3T           ANGLE OF THROW         60°           ANGLE OF THROW         Flatted (6.35mm Dia)	TERMINATION STYLE	Solder Lug
OTHER NAMES         Q5484035           OPERATING FORCE         5.761 ~ 83gfm           NUMBER OF POSITIONS         3           NUMBER OF POLES PER DECK         1           NUMBER OF DECKS         1           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           INDEX STOPS         Fixed           FEATURES         -           DETAILED DESCRIPTION         Rotary Switch 3 Position SP3T SA (AC), 1A (DC) 115VAC Panel Mount           DETH BEHIND PANEL         26.04mm           CURRENT RATING         SA (AC), 1A (DC)           CONTACT TIMING         Non-Shorting (BBM)           CONTACT TIMISH         -           CONTACT FINISH         -           CURCUIT PER DECK         593T           ANGLE OF THROW         60°           ACHUATOR TYPE         Flatted (6.35mm Dia)	SERIES	44
OPERATING FORCE         5.761 ~ 83gfm           NUMBER OF POSITIONS         3           NUMBER OF POLES PER DECK         1           NUMBER OF DECKS         1           MOUNTING TYPE         Panel Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           INDEX STOPS         Fixed           FEATURES         -           DETAILED DESCRIPTION         Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount           DETH BEHIND PANEL         26.04mm           CURRENT RATING         5A (AC), 1A (DC)           CONTACT TIMING         Non-Shorting (BBM)           CONTACT TIMING         Silver Alloy           CONTACT MATERIAL         Silver Alloy           CONTACT FINISH         -           CIRCUIT PER DECK         SP3T           ANGLE OF THROW         60°           ANGLE OF THROW         Flatted (6.35mm Dia)	PANEL CUTOUT DIMENSIONS	-
NUMBER OF POSITIONS  NUMBER OF POLES PER DECK  NUMBER OF DECKS  MOUNTING TYPE  MOUNTING TYPE  MOUNTING TYPE  MOUNTING SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  INDEX STOPS  Fixed  FEATURES  DETAILED DESCRIPTION  ACTOR SWINT SPATS A (AC), 1A (DC) 115VAC Panel Mount  CURRENT RATING  CONTACT TIMING  CONTACT TIMING  CONTACT TIMING  CONTACT TIMING  CONTACT TIMING  CONTACT PER DECK  CONTACT PER DECK  ANGLE OF THROW  FIXED  FIXED  FIXED  FIXED  ANGLE OF THROW  ANGLE OF THROW  ANGLE OF THROW  ANGLE OF STATUS A (AC), 1A (DC)  FIXED  FIXED	OTHER NAMES	Q5484035
NUMBER OF POLES PER DECK1NUMBER OF DECKS1MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel MountDEPTH BEHIND PANEL5A (AC), 1A (DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT TIMINGSilver AlloyCONTACT FINISH-CONTACT FINISH-CIRCUIT PER DECKSP3TANGLE OF THROWHatted (6.55mm Dia)	OPERATING FORCE	5.761 ~ 83gfm
NUMBER OF DECKS1MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel MountCURRENT RATING5A (AC), 1A (DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALSilver AlloyCONTACT FINISH-CIRCUIT PER DECKSP3TANGLE OF THROW60°ANGLE OF THROWFlatted (6.35mm Dia)	NUMBER OF POSITIONS	3
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS FEATURES FEATURES DETAILED DESCRIPTION ROTARY SWITCH 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount  CURRENT RATING CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH CURCUIT PER DECK ANGLE OF THROW ANGLE OF THROW FILLED DESCRIPTION  ROTE OF GOOD FILLED DESCRIPTION FILLED D	NUMBER OF POLES PER DECK	1
MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  INDEX STOPS Fixed  FEATURES  DETAILED DESCRIPTION ROADS STATUS ROADS POSITION SP3T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL 26.04mm  CURRENT RATING 5A (AC), 1A (DC)  CONTACT TIMING Non-Shorting (BBM)  CONTACT TIMING Silver Alloy  CONTACT FINISH  CIRCUIT PER DECK SP3T  ANGLE OF THROW 60°  Flatted (6.35mm Dia)	NUMBER OF DECKS	1
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel MountDEPTH BEHIND PANEL26.04mmCURRENT RATING5A (AC), 1A (DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALSilver AlloyCONTACT FINISH-CIRCUIT PER DECKSP3TANGLE OF THROW60°ACTUATOR TYPEFlatted (6.35mm Dia)	MOUNTING TYPE	Panel Mount
FEATURES - CACTUATORY PER DECK PTION PANEL SO POSITION PO	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FEATURES  DETAILED DESCRIPTION  ROTATY SWITCH 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL  CURRENT RATING  CONTACT TIMING  CONTACT TIMING  CONTACT FINISH  CONTACT FINISH  CIRCUIT PER DECK  ANGLE OF THROW  ACTUATOR TYPE  FIATURES  ROTATOR SWITCH A POSITION SP3T 5A (AC), 1A (DC) 115VAC Panel Mount  CONTACT MATERIAL  SA (AC), 1A (DC)  ANDLE SMITH SMIT	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING SA (AC), 1A (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DEMAND SA (AC), 1A (DC) 115VAC Panel Mount SA (AC), 1A (DC) 115VAC Panel Mount SA (AC), 1A (DC) 115VAC Panel Mount SA (AC), 1A (DC) SA	INDEX STOPS	Fixed
DEPTH BEHIND PANEL 26.04mm  CURRENT RATING 5A (AC), 1A (DC)  CONTACT TIMING Non-Shorting (BBM)  CONTACT MATERIAL Silver Alloy  CONTACT FINISH - CONTACT PER DECK SP3T  ANGLE OF THROW 60°  ACTUATOR TYPE FIRED SILVER SILVE	FEATURES	-
CURRENT RATING  SA (AC), 1A (DC)  CONTACT TIMING  Non-Shorting (BBM)  CONTACT MATERIAL  Silver Alloy  CONTACT FINISH  CIRCUIT PER DECK  ANGLE OF THROW  ACTUATOR TYPE  SA (AC), 1A (DC)  Non-Shorting (BBM)  Silver Alloy  Silver Alloy  60°  Flatted (6.35mm Dia)	DETAILED DESCRIPTION	Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount
CONTACT TIMING Non-Shorting (BBM)  CONTACT MATERIAL Silver Alloy  CONTACT FINISH CIRCUIT PER DECK SP3T  ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	DEPTH BEHIND PANEL	26.04mm
CONTACT MATERIAL  CONTACT FINISH  CIRCUIT PER DECK  ANGLE OF THROW  ACTUATOR TYPE  Flatted (6.35mm Dia)	CURRENT RATING	5A (AC), 1A (DC)
CONTACT FINISH  CIRCUIT PER DECK  SP3T  ANGLE OF THROW  ACTUATOR TYPE  Flatted (6.35mm Dia)	CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECK ANGLE OF THROW 60° ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT MATERIAL	Silver Alloy
ANGLE OF THROW 60°  ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT FINISH	-
ACTUATOR TYPE Flatted (6.35mm Dia)	CIRCUIT PER DECK	SP3T
	ANGLE OF THROW	60°
ACTUATOR LENGTH 11.10mm	ACTUATOR TYPE	Flatted (6.35mm Dia)
	ACTUATOR LENGTH	11.10mm

# **Related Tags**

Construction of Admics of	44MC0 01 1 02N Distributor	44MC0 04 1 02N Consultan
Grayhill, Inc. 44M60-01-1-03N	44M60-01-1-03N Distributor	44M60-01-1-03N Supplier
44M60-01-1-03N Price	44M60-01-1-03N Pictures	44M60-01-1-03N Image
44M60-01-1-03N PDF Datasheet	44M60-01-1-03N Download Datasheet	44M60-01-1-03N Datasheet
44M60-01-1-03N Stock	Buy 44M60-01-1-03N	Buy Grayhill, Inc. 44M60-01-1-03N
Grayhill, Inc. 44M60-01-1-03N	Grayhill, Inc. Supplier	Grayhill, Inc. Distributor
Grayhill, Inc. 44M60-01-1-03N	Grayhill Inc. 44M60-01-1-03N	

# **Related Products**



## 44M45-12-1-03N

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 45 DEG 1

In stock: 470 pcs

**RFQ** 



44M60-01-1-02N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 60 DEG 1 In stock: 1881 pcs

**RFQ** 

Grayhill

### 44M45-12-1-08N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 1 In stock: 501 pcs

**RFQ** 



# 44M60-01-3-02N

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 60 DEG 1

In stock: 1408 pcs

**RFQ** 



## 44M45-12B08N

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 45 DEG 1

In stock: 424 pcs

**RFQ** 



#### 44M60-01-1-05N Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 60 DEG 1

In stock: 1533 pcs

**RFQ** 



### 44M45-12-1-07N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 1 In stock: 393 pcs

**RFQ** 



Grayhill

## Manufacturers: Grayhill, Inc.

44M60-01-2-02N

Description: SWITCH ROTARY 85 DEG;C, 60 DEG 1 In stock: 1708 pcs

**RFQ** 



#### Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 60 DEG 1

44M60-01-2-03N

In stock: 1371 pcs

**RFQ** 



#### Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 60 DEG 1

44M60-01-1-04N

In stock: 1803 pcs **RFQ** 

44M60-01-1-06N




### 44M45-12-1-06N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 1 In stock: 449 pcs

Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong

**RFQ** 





Manufacturers: Grayhill, Inc.

**RFQ** 

In stock: 1423 pcs











