## N/A Image may be representation. See specifications for product details.

## SN65LVDT390PWR

Part Number:

Product description

Datasheets:

Manufacturer/Brand:

RoHs Status Stock Condition

Ship From Shipment Way SN65LVDT390PWR

N/A

IC DIFF LINE RECEIVER HS 16TSSOP

Lead free / RoHS Compliant

60058 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

PART NUMBER SN6SLVDT390PWR  MANUFACTURER N/A  DESCRIPTION IC DIFF LINE RECEIVER HS 16TSSOP  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  QUANTITY AVAILABLE 60058 pcs  DATA SHEET  VOLTAGE - SUPPLY 3 V ~ 3.6 V  TYPE Receiver  SUPPLIER DEVICE PACKAGE 16-TSSOP  SERIES 65LVDT  PACKAGING Tape & Reel (TR)  PACKAGING Tape & Reel (TR)  PACKAGE / CASE 16-TSSOP (0.173", 4.40mm Width)  OTHER NAMES 296-46334-2 SN6SLVDT390PWR-ND  OPERATING TEMPERATURE 40°C ~ 85°C  NUMBER OF DRIVERS/RECEIVERS 0/4  MOUNTING TYPE Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  DUPLEX - DETAILED DESCRIPTION 0/4 Receiver LVDS 16-TSSOP  DATA RATE 200Mbps  BASE PART NUMBER		Specifications of SN65LVDT390PWR
MANUFACTURER  DESCRIPTION  IC DIFF LINE RECEIVER HS 16TSSOP  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  QUANTITY AVAILABLE  60058 pcs  DATA SHEET  VOLTAGE - SUPPLY  3 V ~ 3.6 V  TYPE  Receiver  SUPPLIER DEVICE PACKAGE  16-TSSOP  SERIES  65LVDT  PROTOCOL  LVDS  PACKAGING  Tape & Reel (TR)  PACKAGE / CASE  16-TSSOP (0.173", 4.40mm Width)  OTHER NAMES  296-46334-2 SN65LVDT390PWR-ND  OPERATING TEMPERATURE  -40°C ~ 85°C  NUMBER OF DRIVERS/RECEIVERS  0/4  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD free / ROHS Compliant  DUPLEX  - DETAILED DESCRIPTION  0/4 Receiver LVDS 16-TSSOP  DATA RATE  200Mbps		Specifications of Sixoseve 19501 VIII
DESCRIPTION  IC DIFF LINE RECEIVER HS 16TSSOP  Lead free / ROHS Compliant  QUANTITY AVAILABLE  60058 pcs  DATA SHEET  VOLTAGE - SUPPLY  3 V ~ 3.6 V  TYPE  Receiver  SUPPLIER DEVICE PACKAGE  16-TSSOP  SERIES  65LVDT  PROTOCOL  LVDS  PACKAGING  Tape & Reel (TR)  PACKAGE / CASE  16-TSSOP (0.173", 4.40mm Width)  OTHER NAMES  OPERATING TEMPERATURE  AUOV ~ 85°C  NUMBER OF DRIVERS/RECEIVERS  MOUNTING TYPE  MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD free / ROHS Compliant  DUPLEX  - DETAILED DESCRIPTION  0/4 Receiver LVDS 16-TSSOP  DATA RATE  200Mbps	PART NUMBER	SN65LVDT390PWR
LEAD FREE STATUS / ROHS STATUS     Lead free / RoHS Compliant       QUANTITY AVAILABLE     60058 pcs       DATA SHEET     ************************************	MANUFACTURER	N/A
QUANTITY AVAILABLE60058 pcsDATA SHEETVOLTAGE - SUPPLY3 V ~ 3.6 VTYPEReceiverSUPPLIER DEVICE PACKAGE16-TSSOPSERIES65LVDTPROTOCOLLVDSPACKAGINGTape & Reel (TR)PACKAGE / CASE16-TSSOP (0.173", 4.40mm Width)OTHER NAMES296-46334-2 SN65LVDT390PWR-NDOPERATING TEMPERATURE40°C ~ 85°CNUMBER OF DRIVERS/RECEIVERS0/4MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantDUPLEX-DETAILED DESCRIPTION0/4 Receiver LVDS 16-TSSOPDATA RATE200Mbps	DESCRIPTION	IC DIFF LINE RECEIVER HS 16TSSOP
VOLTAGE - SUPPLY VOLTAGE - SUPPLY XV 3 V ~ 3.6 V  YPE Receiver SUPPLIER DEVICE PACKAGE SERIES SERIES SERIES SERIES SERIES FROTOCOL VDS PACKAGING PACKAGING PACKAGING VOHER NAMES VOHER NAMES VOHER NAMES VOHER NAMES VOHER NAMES VOHER SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DUPLEX DETAILED DESCRIPTION VOHER NAMES VOA 3 V ~ 3.6 V  Receiver VOA 3 V ~ 3.6 V  Receiver VOB SENSITIVATION  AV ~ 3.6 V  Receiver VOB SENSITIVATION  AV ~ 3.6 V  Receiver VDS VDB VDB VDB VDB VDB VDB VDB VC ~ 85°C VDB	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE - SUPPLY  TYPE  Receiver  SUPPLIER DEVICE PACKAGE  65LVDT  PROTOCOL  PROTOCOL  PACKAGING  PACKAGING  Tape & Reel (TR)  PACKAGE / CASE  16-TSSOP (0.173", 4.40mm Width)  OTHER NAMES  OPERATING TEMPERATURE  A0°C ~ 85°C  NUMBER OF DRIVERS/RECEIVERS  MOUNTING TYPE  MOUNTING TYPE  MOUNTING TYPE  MOUSTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  DETAILED DESCRIPTION  DOHAR ARE  DETAILED DESCRIPTION  DOMBOR  DOMBOR  DOMBOR  SWA 3.6 V  AV ~ 3.6 V  ACCEIVER	QUANTITY AVAILABLE	60058 pcs
TYPEReceiverSUPPLIER DEVICE PACKAGE16-TSSOPSERIES65LVDTPROTOCOLLVDSPACKAGINGTape & Reel (TR)PACKAGE / CASE16-TSSOP (0.173", 4.40mm Width)OTHER NAMES296-46334-2OPERATING TEMPERATURE40°C ~ 85°CNUMBER OF DRIVERS/RECEIVERS0/4MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantDUPLEX-DETAILED DESCRIPTION0/4 Receiver LVDS 16-TSSOPDATA RATE200Mbps	DATA SHEET	
SUPPLIER DEVICE PACKAGE  SERIES  65LVDT  PROTOCOL  LVDS  PACKAGING  PACKAGING  PACKAGING  16-TSSOP (0.173", 4.40mm Width)  OTHER NAMES  OTHER NAMES  OPERATING TEMPERATURE  A0°C ~ 85°C  NUMBER OF DRIVERS/RECEIVERS  MOUNTING TYPE  MOUSTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  DUPLEX  DUPLEX  DETAILED DESCRIPTION  DATA RATE  16-TSSOP  AUDIT  ADE RECEIVERS  ALEA RECEIVERS  ALEA GERMEN  BOMBS  16-TSSOP  AUDIT  ADE RECEIVERS  ADE RECEIVERS  ALEA GERMEN  A	VOLTAGE - SUPPLY	3 V ~ 3.6 V
SERIES65LVDTPROTOCOLLVDSPACKAGINGTape & Reel (TR)PACKAGE / CASE16-TSSOP (0.173", 4.40mm Width)OTHER NAMES296-46334-2 SN65LVDT390PWR-NDOPERATING TEMPERATURE40°C ~ 85°CNUMBER OF DRIVERS/RECEIVERS0/4MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantDUPLEX-DETAILED DESCRIPTION0/4 Receiver LVDS 16-TSSOPDATA RATE200Mbps	TYPE	Receiver
PROTOCOL  PACKAGING  PACKAGE / CASE  16-TSSOP (0.173", 4.40mm Width)  OTHER NAMES  OPERATING TEMPERATURE  NUMBER OF DRIVERS/RECEIVERS  MOUNTING TYPE  MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  DUPLEX  DETAILED DESCRIPTION  MOH RECEIVERS  DATA RATE  LVDS  1	SUPPLIER DEVICE PACKAGE	16-TSSOP
PACKAGING Tape & Reel (TR)  PACKAGE / CASE 16-TSSOP (0.173", 4.40mm Width)  OTHER NAMES 296-46334-2 SN65LVDT390PWR-ND  OPERATING TEMPERATURE -40°C ~ 85°C  NUMBER OF DRIVERS/RECEIVERS 0/4  MOUNTING TYPE SURface Mount  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  DUPLEX -  DETAILED DESCRIPTION 0/4 Receiver LVDS 16-TSSOP  DATA RATE 200Mbps	SERIES	65LVDT
PACKAGE / CASE  16-TSSOP (0.173", 4.40mm Width)  16-TSSOP (0.173", 4.40mm Width)  296-46334-2 SN65LVDT390PWR-ND  OPERATING TEMPERATURE  -40°C ~ 85°C  NUMBER OF DRIVERS/RECEIVERS  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD free / ROHS Compliant  DUPLEX  DETAILED DESCRIPTION  O/4 Receiver LVDS 16-TSSOP  DATA RATE  296-46334-2 SN65LVDT390PWR-ND SN65LV	PROTOCOL	LVDS
OTHER NAMES296-46334-2 SN65LVDT390PWR-NDOPERATING TEMPERATURE-40°C ~ 85°CNUMBER OF DRIVERS/RECEIVERS0/4MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantDUPLEX-DETAILED DESCRIPTION0/4 Receiver LVDS 16-TSSOPDATA RATE200Mbps	PACKAGING	Tape & Reel (TR)
OPERATING TEMPERATURE -40°C ~ 85°C  NUMBER OF DRIVERS/RECEIVERS 0/4  MOUNTING TYPE Sunsitivity Level (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant  DUPLEX -  DETAILED DESCRIPTION 0/4 Receiver LVDS 16-TSSOP  DATA RATE 200Mbps	PACKAGE / CASE	16-TSSOP (0.173", 4.40mm Width)
NUMBER OF DRIVERS/RECEIVERS0/4MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantDUPLEX-DETAILED DESCRIPTION0/4 Receiver LVDS 16-TSSOPDATA RATE200Mbps	OTHER NAMES	
MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  DUPLEX  DETAILED DESCRIPTION  O/4 Receiver LVDS 16-TSSOP  DATA RATE  Surface Mount  1 (Unlimited)  1 (Unlimited)  200Mbps	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  DUPLEX  DETAILED DESCRIPTION  O/4 Receiver LVDS 16-TSSOP  DATA RATE  200Mbps	NUMBER OF DRIVERS/RECEIVERS	0/4
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantDUPLEX-DETAILED DESCRIPTION0/4 Receiver LVDS 16-TSSOPDATA RATE200Mbps	MOUNTING TYPE	Surface Mount
DUPLEX DETAILED DESCRIPTION O/4 Receiver LVDS 16-TSSOP DATA RATE 200Mbps	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
DETAILED DESCRIPTION 0/4 Receiver LVDS 16-TSSOP  DATA RATE 200Mbps	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DATA RATE 200Mbps	DUPLEX	-
·	DETAILED DESCRIPTION	0/4 Receiver LVDS 16-TSSOP
BASE PART NUMBER SN65LVDT390	DATA RATE	200Mbps
	BASE PART NUMBER	SN65LVDT390

## **Related Tags**

SN65LVDT390PWR	SN65LVDT390PWR Distributor	SN65LVDT390PWR Supplier
SN65LVDT390PWR Price	SN65LVDT390PWR Pictures	SN65LVDT390PWR Image
SN65LVDT390PWR PDF Datasheet	SN65LVDT390PWR Download Datasheet	SN65LVDT390PWR Datasheet
SN65LVDT390PWR Stock	Buy SN65LVDT390PWR	Buy SN65LVDT390PWR
SN65LVDT390PWR	Supplier	Distributor

**Related Products** 

