product details.

linfinity-electronic

N/A	SN75LBC172DWR	
	Part Number:	
	Manufacturer/Brand:	
	Product description	
	Datasheets:	
	RoHs Status	
	Stock Condition	
	Ship From	
	Shipment Way	
	REQUEST FOR QUOTATIO	DN

SN75LBC172DWR

N/A IC DIFF LINE DRVR QUAD LP 20SOIC

Lead free / RoHS Compliant 45494 pcs stock Hong Kong DHL/Fedex/TNT/UPS/EMS

Specifications of SN75LBC172DWR

NANUFACTURERNADESCRIPTIONCDIFF LINE DRVR QUAD LP 20SOICLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantQUANTITY AVAILABLEdef ree / ROHS CompliantDATA SHEETVOLTAGE - SUPPLYVOLTAGE - SUPPLYA.55 VSUPLIER DEVICE PACKAGE0*50°CSUPPLIER DEVICE PACKAGE0*50°CSRIES-PROTOCOLRA22, RS485PACKAGE / CASE0*50°C (205°T, SOMM Width)OTHER NAMES0*50°C (205°T, SOMM Width)OTHER NAMES0*50°C (205°T, SOMM Width)OPERATING TEMPERATURE0°C * 0°CNUMER OF DRIVERS/RECEIVERS4/0MOUNTING TYPE0/10°CMOUNTING TYPE(1/10°C)MOUNTING TYPE<																																																								
DESCRIPTIONIC DIFF LINE DRVR QUAD LP 20SOICLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantQUANTITY AVAILABLE4549 dpcDATA SHET.VOLTAGE - SUPPLYA.75 V ~ 5.5 VSUPPLIER DEVICE PACKAGE0 FORSUPPLIER DEVICE PACKAGE0-SOICSRIES.PACKAGINGMERA (TR)PACKAGE / CASE0-SOIC (D.257, J.50m Width)OTHER NAMES0-SOIC (D.257, J.50m Width)OTHER NAMES0-SOIC (D.257, J.50m Width)OPERATING TEMPERATURE0-C ~ 0°CNUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPE0-SIG MOUNTING TYPEMOUNTING TYPEU.10IIIICAL (MELLA)MOUNTING TYPEU.10IIIICAL (MELLA)MICH EN STATUSU.10IIIICAL (MELLA)MICH EN STATUSU.10IIIICAL (MELLA)MICH EN STATUSU.10IIIICAL (MELLA)	PART NUMBER	SN75LBC172DWR																																																						
LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantQUANTITY AVAILABLE4549 ccDATA SHEET75 v S 25 VVOLTAGE - SUPPLYA75 v S 25 VSTPLER DEVICE PACKAGE0vorSUPPLIER DEVICE PACKAGE0-SOICPROTOCOLR542, R5485PACKAGE / CASE0-SOIC 0.25 V, STOM Width)PACKAGE / CASE0-SOIC 0.25 V, STOM Width)OPERATING TEMPERATURE0-SOIC 0.25 V, STOM Width)OPERATING TEMPERATURE0-SOIC 0.25 V, STOM Width)OPERATING TEMPERATURE0-SOIC 0.25 V, STOM Width)OUNTING TYPE0-SOIC 0.25 V, STOM Width)MOUNTING TYPE0-SOIC 0.25 V, STOM WIDTH)MOUNTING TYPE0-SIGE 0.25 V, STOM WIDTH) <tr <td="">MOUNTING TYPE<td>MANUFACTURER</td><td>N/A</td></tr> <tr><td>QUANTLY AVALLABLE5494 pcsDATA SHEFTK194 pcsVOLTAGE - SUPPLYA55 x - S.2 x - S.2</td><td>DESCRIPTION</td><td>IC DIFF LINE DRVR QUAD LP 20SOIC</td></tr> <tr><td>DATA SHEETVOLTAGE - SUPPLY4.75 V ~ 5.25 VTYPEDriverSUPPLIER DEVICE PACKAGE0-SOICSREES-PROTOCOLR542, R5485PACKAGINGTap & Reel (TR)PACKAGE / CASE0-SOIC (0.295", 7.50mm Width)OTHER NAMES0-SOIC (0.295", 7.50mm Width)OPERATING TEMPERATURE0-C ~ 0°CNUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPE1.01mited MountMOUNTING TYPE1.01mited MountMOUNT MOUNT MO</td><td>LEAD FREE STATUS / ROHS STATUS</td><td>Lead free / RoHS Compliant</td></tr> <tr><td>Voltage - SUPPLY475 × 525 VTYPEDiverSUPPLIER DEVICE PACKAGE0-SOCSERIES-PACKAGINGK822, R5455PACKAGINGTop & Rel (TR)PACKAGE / CASE0-SOC (0.295", 7.50m Width)OTHER NAMES0-SOC (0.295", 7.50m Width)OTHER NAMES0-C ~ 0°CNUMER OF DRIVERS/RECEIVERS0-C ~ 0°CMOUNTING TYPESuface MountMOUNTING TYPEU (101104)MOUNTING T</td><td>QUANTITY AVAILABLE</td><td>45494 pcs</td></tr> <tr><td>TYEDiverSUPLIER DEVICE PACKAGEDesolutionSRIES-PROTOCOLR42, R485PACKAGINGDesolutionPACKAGE / CASE-DIVER NAMESDesolutionOFERTING TEMPERATURE0° C 20°CNUMER OF DRIVERS/RECEIVERSOffice MonteMOUNTING TYPELinite MonteMOSTURE SENSITIVITY LEVEL (MSL)Linite MonteLEAD FRE SENSITIVITY LEVEL (MSL)Linite MonteMARE SENSITIVITY LEVEL (MSL)Linite MonteMA</td><td>DATA SHEET</td><td></td></tr> <tr><td>SUPPLIER DEVICE PACKAGE 20-SOIC SERIES</td><td>VOLTAGE - SUPPLY</td><td>4.75 V ~ 5.25 V</td></tr> <tr><td>SERIES-PROTOCOLR542, R5485PACKAGINGTape Ren (TR)PACKAGE / CASE0-SOIC (0.255", 7.50mm Width)OTHER NAMESSN5LEG12DWRG4-NDOPERATING TEMPERATURE0° ~ 70°NUMBER OF DRIVERS/RECEIVERS0/MOUNTING TYPEJuface MountMOISTURE SENSITIVITY LEVEL (MSL)1(Jimited)LED FRES TATUS / ROHSEd FE (SCH)</td><td>TYPE</td><td>Driver</td></tr> <tr><td>PROTOCOL R422, R5485 PACKAGING Tape Real (TR) PACKAGE / CASE 0-502 (0.295", 7.50mm Width) other NAMES 0-602 (0.295", 7.50mm Width) NUMBER OF DRIVERS/RECEIVERS 0-602 (0.295", 7.50mm Width) MOUNTING TYPE 0-602 (0.295", 7.50mm Width) MOISTURE SENSITIVELY LEVEL (MSL) 0-1010 (0.295", 7.50mm Width) Ital Park Sensitive Sensitiv</td><td>SUPPLIER DEVICE PACKAGE</td><td>20-SOIC</td></tr> <tr><td>PACKAGING Tape & Reel (TR) PACKAGE / CASE 0-SOIC (0.295", 7.50mm Width) OTHER NAMES SN5LBC122DWRG4-ND OPERATING TEMPERATURE 0°C ~ 70°C NUMBER OF DRIVERS/RECEIVERS 6/G MOUNTING TYPE Suface Mount MOISTURE SENSITITYT LEVEL (MSL) 1 (Unimited) LEAD FRE STATUS / ROHS STATUS Ead fre / ROHS Compliant</td><td>SERIES</td><td>-</td></tr> <tr><td>PACKAGE / CASEDescriptionother NAMESShSLBC12DWRG4 ShSLBC12DWRG4 ShSLBC12DWRG4 NDWBER OF DRIVERS/RECEIVERSNUMBER OF DRIVERS/RECEIVERS40MOUNTING TYPESurface Mountain Sinface MountainNOTSTURE SINSTITUTY LEVEL (MSL)1 (Unimited)LAD FREE STATUS / ROHS STATUSEdife / ROHS Compliant</br></td><td>PROTOCOL</td><td>RS422, RS485</td></tr> <tr><td>oTHER NAMESSN75LBC172DWRG4-NDOPERATING TEMPERATURE0°C ~ 70°CNUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSEad free / ROHS Compliant</td><td>PACKAGING</td><td>Tape & Reel (TR)</td></tr> <tr><td>OTHER NAMES SN75LBC172DWRG4-ND OPERATING TEMPERATURE 0°C ~ 70°C NUMBER OF DRIVERS/RECEIVERS 4/0 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant</td><td>PACKAGE / CASE</td><td>20-SOIC (0.295", 7.50mm Width)</td></tr> <tr><td>NUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / RoHS Compliant</td><td>OTHER NAMES</td><td></td></tr> <tr><td>MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant</td><td>OPERATING TEMPERATURE</td><td>0°C ~ 70°C</td></tr> <tr><td>MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant</td><td>NUMBER OF DRIVERS/RECEIVERS</td><td>4/0</td></tr> <tr><td>LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant</td><td>MOUNTING TYPE</td><td>Surface Mount</td></tr> <tr><td></td><td>MOISTURE SENSITIVITY LEVEL (MSL)</td><td>1 (Unlimited)</td></tr> <tr><td>DUPLEX -</td><td>LEAD FREE STATUS / ROHS STATUS</td><td>Lead free / RoHS Compliant</td></tr> <tr><td></td><td>DUPLEX</td><td>-</td></tr>	MANUFACTURER	N/A	QUANTLY AVALLABLE5494 pcsDATA SHEFTK194 pcsVOLTAGE - SUPPLYA55 x - S.2	DESCRIPTION	IC DIFF LINE DRVR QUAD LP 20SOIC	DATA SHEETVOLTAGE - SUPPLY4.75 V ~ 5.25 VTYPEDriverSUPPLIER DEVICE PACKAGE0-SOICSREES-PROTOCOLR542, R5485PACKAGINGTap & Reel (TR)PACKAGE / CASE0-SOIC (0.295", 7.50mm Width)OTHER NAMES0-SOIC (0.295", 7.50mm Width)OPERATING TEMPERATURE0-C ~ 0°CNUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPE1.01mited MountMOUNTING TYPE1.01mited MountMOUNT MOUNT MO	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	Voltage - SUPPLY475 × 525 VTYPEDiverSUPPLIER DEVICE PACKAGE0-SOCSERIES-PACKAGINGK822, R5455PACKAGINGTop & Rel (TR)PACKAGE / CASE0-SOC (0.295", 7.50m Width)OTHER NAMES0-SOC (0.295", 7.50m Width)OTHER NAMES0-C ~ 0°CNUMER OF DRIVERS/RECEIVERS0-C ~ 0°CMOUNTING TYPESuface MountMOUNTING TYPEU (101104)MOUNTING T	QUANTITY AVAILABLE	45494 pcs	TYEDiverSUPLIER DEVICE PACKAGEDesolutionSRIES-PROTOCOLR42, R485PACKAGINGDesolutionPACKAGE / CASE-DIVER NAMESDesolutionOFERTING TEMPERATURE0° C 20°CNUMER OF DRIVERS/RECEIVERSOffice MonteMOUNTING TYPELinite MonteMOSTURE SENSITIVITY LEVEL (MSL)Linite MonteLEAD FRE SENSITIVITY LEVEL (MSL)Linite MonteMARE SENSITIVITY LEVEL (MSL)Linite MonteMA	DATA SHEET		SUPPLIER DEVICE PACKAGE 20-SOIC SERIES	VOLTAGE - SUPPLY	4.75 V ~ 5.25 V	SERIES-PROTOCOLR542, R5485PACKAGINGTape Ren (TR)PACKAGE / CASE0-SOIC (0.255", 7.50mm Width)OTHER NAMESSN5LEG12DWRG4-NDOPERATING TEMPERATURE0° ~ 70°NUMBER OF DRIVERS/RECEIVERS0/MOUNTING TYPEJuface MountMOISTURE SENSITIVITY LEVEL (MSL)1(Jimited)LED FRES TATUS / ROHSEd FE (SCH)	TYPE	Driver	PROTOCOL R422, R5485 PACKAGING Tape Real (TR) PACKAGE / CASE 0-502 (0.295", 7.50mm Width) other NAMES 0-602 (0.295", 7.50mm Width) NUMBER OF DRIVERS/RECEIVERS 0-602 (0.295", 7.50mm Width) MOUNTING TYPE 0-602 (0.295", 7.50mm Width) MOISTURE SENSITIVELY LEVEL (MSL) 0-1010 (0.295", 7.50mm Width) Ital Park Sensitive Sensitiv	SUPPLIER DEVICE PACKAGE	20-SOIC	PACKAGING Tape & Reel (TR) PACKAGE / CASE 0-SOIC (0.295", 7.50mm Width) OTHER NAMES SN5LBC122DWRG4-ND OPERATING TEMPERATURE 0°C ~ 70°C NUMBER OF DRIVERS/RECEIVERS 6/G MOUNTING TYPE Suface Mount MOISTURE SENSITITYT LEVEL (MSL) 1 (Unimited) LEAD FRE STATUS / ROHS STATUS Ead fre / ROHS Compliant	SERIES	-	PACKAGE / CASEDescriptionother NAMESShSLBC12DWRG4 ShSLBC12DWRG4 ShSLBC12DWRG4 NDWBER OF DRIVERS/RECEIVERSNUMBER OF DRIVERS/RECEIVERS40MOUNTING TYPESurface Mountain 	PROTOCOL	RS422, RS485	oTHER NAMESSN75LBC172DWRG4-NDOPERATING TEMPERATURE0°C ~ 70°CNUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSEad free / ROHS Compliant	PACKAGING	Tape & Reel (TR)	OTHER NAMES SN75LBC172DWRG4-ND OPERATING TEMPERATURE 0°C ~ 70°C NUMBER OF DRIVERS/RECEIVERS 4/0 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant	PACKAGE / CASE	20-SOIC (0.295", 7.50mm Width)	NUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / RoHS Compliant	OTHER NAMES		MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant	OPERATING TEMPERATURE	0°C ~ 70°C	MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant	NUMBER OF DRIVERS/RECEIVERS	4/0	LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant	MOUNTING TYPE	Surface Mount		MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)	DUPLEX -	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant		DUPLEX	-
MANUFACTURER	N/A																																																							
QUANTLY AVALLABLE5494 pcsDATA SHEFTK194 pcsVOLTAGE - SUPPLYA55 x - S.2	DESCRIPTION	IC DIFF LINE DRVR QUAD LP 20SOIC																																																						
DATA SHEETVOLTAGE - SUPPLY4.75 V ~ 5.25 VTYPEDriverSUPPLIER DEVICE PACKAGE0-SOICSREES-PROTOCOLR542, R5485PACKAGINGTap & Reel (TR)PACKAGE / CASE0-SOIC (0.295", 7.50mm Width)OTHER NAMES0-SOIC (0.295", 7.50mm Width)OPERATING TEMPERATURE0-C ~ 0°CNUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPE1.01mited MountMOUNTING TYPE1.01mited MountMOUNT MOUNT MO	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant																																																						
Voltage - SUPPLY475 × 525 VTYPEDiverSUPPLIER DEVICE PACKAGE0-SOCSERIES-PACKAGINGK822, R5455PACKAGINGTop & Rel (TR)PACKAGE / CASE0-SOC (0.295", 7.50m Width)OTHER NAMES0-SOC (0.295", 7.50m Width)OTHER NAMES0-C ~ 0°CNUMER OF DRIVERS/RECEIVERS0-C ~ 0°CMOUNTING TYPESuface MountMOUNTING TYPEU (101104)MOUNTING T	QUANTITY AVAILABLE	45494 pcs																																																						
TYEDiverSUPLIER DEVICE PACKAGEDesolutionSRIES-PROTOCOLR42, R485PACKAGINGDesolutionPACKAGE / CASE-DIVER NAMESDesolutionOFERTING TEMPERATURE0° C 20°CNUMER OF DRIVERS/RECEIVERSOffice MonteMOUNTING TYPELinite MonteMOSTURE SENSITIVITY LEVEL (MSL)Linite MonteLEAD FRE SENSITIVITY LEVEL (MSL)Linite MonteMARE SENSITIVITY LEVEL (MSL)Linite MonteMA	DATA SHEET																																																							
SUPPLIER DEVICE PACKAGE 20-SOIC SERIES	VOLTAGE - SUPPLY	4.75 V ~ 5.25 V																																																						
SERIES-PROTOCOLR542, R5485PACKAGINGTape Ren (TR)PACKAGE / CASE0-SOIC (0.255", 7.50mm Width)OTHER NAMESSN5LEG12DWRG4-NDOPERATING TEMPERATURE0° ~ 70°NUMBER OF DRIVERS/RECEIVERS0/MOUNTING TYPEJuface MountMOISTURE SENSITIVITY LEVEL (MSL)1(Jimited)LED FRES TATUS / ROHSEd FE (SCH)	TYPE	Driver																																																						
PROTOCOL R422, R5485 PACKAGING Tape Real (TR) PACKAGE / CASE 0-502 (0.295", 7.50mm Width) other NAMES 0-602 (0.295", 7.50mm Width) NUMBER OF DRIVERS/RECEIVERS 0-602 (0.295", 7.50mm Width) MOUNTING TYPE 0-602 (0.295", 7.50mm Width) MOISTURE SENSITIVELY LEVEL (MSL) 0-1010 (0.295", 7.50mm Width) Ital Park Sensitive Sensitiv	SUPPLIER DEVICE PACKAGE	20-SOIC																																																						
PACKAGING Tape & Reel (TR) PACKAGE / CASE 0-SOIC (0.295", 7.50mm Width) OTHER NAMES SN5LBC122DWRG4-ND OPERATING TEMPERATURE 0°C ~ 70°C NUMBER OF DRIVERS/RECEIVERS 6/G MOUNTING TYPE Suface Mount MOISTURE SENSITITYT LEVEL (MSL) 1 (Unimited) LEAD FRE STATUS / ROHS STATUS Ead fre / ROHS Compliant	SERIES	-																																																						
PACKAGE / CASEDescriptionother NAMESShSLBC12DWRG4 ShSLBC12DWRG4 ShSLBC12DWRG4 NDWBER OF DRIVERS/RECEIVERSNUMBER OF DRIVERS/RECEIVERS40MOUNTING TYPESurface Mountain 	PROTOCOL	RS422, RS485																																																						
oTHER NAMESSN75LBC172DWRG4-NDOPERATING TEMPERATURE0°C ~ 70°CNUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSEad free / ROHS Compliant	PACKAGING	Tape & Reel (TR)																																																						
OTHER NAMES SN75LBC172DWRG4-ND OPERATING TEMPERATURE 0°C ~ 70°C NUMBER OF DRIVERS/RECEIVERS 4/0 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant	PACKAGE / CASE	20-SOIC (0.295", 7.50mm Width)																																																						
NUMBER OF DRIVERS/RECEIVERS4/0MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / RoHS Compliant	OTHER NAMES																																																							
MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant	OPERATING TEMPERATURE	0°C ~ 70°C																																																						
MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant	NUMBER OF DRIVERS/RECEIVERS	4/0																																																						
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant	MOUNTING TYPE	Surface Mount																																																						
	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)																																																						
DUPLEX -	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant																																																						
	DUPLEX	-																																																						

DETAILED DESCRIPTION

4/0 Driver RS422, RS485 20-SOIC

DATA RATE

BASE PART NUMBER

SN75LBC172

Related Tags

SN75LBC172DWR	SN75LBC172DWR Distributor	SN75LBC172DWR Supplier
SN75LBC172DWR Price	SN75LBC172DWR Pictures	SN75LBC172DWR Image
SN75LBC172DWR PDF Datasheet	SN75LBC172DWR Download Datasheet	SN75LBC172DWR Datasheet
SN75LBC172DWR Stock	Buy SN75LBC172DWR	Buy SN75LBC172DWR
SN75LBC172DWR	Supplier	Distributor

Related Products

