

Honeywell

Honeywe

Honeywell Sensing and

Productivity Solutions

Part Number:

SCC15DN

Manufacturer/Brand: Product description

RoHs Status Stock Condition

Datasheets:

Ship From

Shipment Way

SCC15DN

Honeywell Sensing and Productivity Solutions

SCC DIFF GAUGE 0 PSID TO 15 PSID

Lead free / RoHS Compliant

2820 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

4-SIP Module		Specifications of SCC15DN
MANUFACTURER Honeywell Sensing and Productivity Solutions SCC DIFF GAUGE 0 PSID TO 15 PSID Lead Free STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 2820 pcs DATA SHEET VOLTAGE - SUPPLY SUPPLIER DEVICE PACKAGE SERIES SCC PRESSURE TYPE Differential PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mV OPERATING TEMPERATURE OPERATING PRESSURE MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 m	•	
DESCRIPTION SCC DIFF GAUGE 0 PSID TO 15 PSID LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 2820 pcs DATA SHEET VOLTAGE - SUPPLY SUPPLIER DEVICE PACKAGE - SCC PRESSURE TYPE Differential PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual PACKAGE / CASE OUTPUT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE OPERATING TEMPERATURE MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 10 PSI (103.42 kPa) LEAD FREE STATUS / ROHS STATUS PRESSURE SENSOR 15 PSI (103.42 kPa) DETAILED DESCRIPTION PRESSURE SENSOR 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 to 4-SIP Module	PART NUMBER	SCC15DN
Lead free / RoHS Compliant QUANTITY AVAILABLE 2820 pcs DATA SHEET VOLTAGE - SUPPLY - SUPPLIER DEVICE PACKAGE - SERIES SCC PRESSURE TYPE Differential PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual PACKAGE / CASE OUTPUT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE OPERATING PRESSURE MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 10 Unlimited) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 to 4-SIP Module	MANUFACTURER	Honeywell Sensing and Productivity Solutions
QUANTITY AVAILABLE DATA SHEET VOLTAGE - SUPPLY SUPPLIER DEVICE PACKAGE - SERIES SCC PRESSURE TYPE Differential PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual AMBLE DUTPUT AUDIT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE OPERATING PRESSURE 15 PSI (103.42 kPa) MAXIMUM PRESSURE MAXIMUM PRESSURE Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mV OPERATION OF THE OFFICE OFFICE OF THE OFFICE OF THE OFFICE OF THE OFFICE OFFICE OF THE OFFICE OF THE OFFICE OF THE OFFICE OFFICE OF THE OFFICE OFFICE OFFICE OF THE OFFICE OF	DESCRIPTION	SCC DIFF GAUGE 0 PSID TO 15 PSID
DATA SHEET VOLTAGE - SUPPLY SUPPLIER DEVICE PACKAGE SERIES SCC PRESSURE TYPE Differential PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual PACKAGE / CASE OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE OUTPUT 40 mV ~ 95 mV OPERATING PRESSURE 15 PSI (103.42 kPa) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compensated DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mV DETAILED DESCRIPTION	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE - SUPPLY SUPPLIER DEVICE PACKAGE - SERIES SCC PRESSURE TYPE Differential PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual PACKAGE / CASE 4-SIP Module OUTPUT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mV - 95 mV	QUANTITY AVAILABLE	2820 pcs
SUPPLIER DEVICE PACKAGE SERIES SCC PRESSURE TYPE Differential PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual PACKAGE / CASE 4-SIP Module OUTPUT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant FEATURES DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages of the complex of t	DATA SHEET	
SERIES SCC PRESSURE TYPE Differential PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual PACKAGE / CASE 4-SIP Module OUTPUT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 10 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 manual for the complex of the compl	VOLTAGE - SUPPLY	-
PRESSURE TYPE Differential PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual PACKAGE / CASE 4-SIP Module OUTPUT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant FEATURES DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19"	SUPPLIER DEVICE PACKAGE	-
PORT STYLE Barbed PORT SIZE Male - 0.19" (4.8mm) Tube, Dual PACKAGE / CASE 4-SIP Module OUTPUT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Temperature Compensated Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic description Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic description	SERIES	SCC
PORT SIZE Male - 0.19" (4.8mm) Tube, Dual PACKAGE / CASE 4-SIP Module OUTPUT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES DETAILED DESCRIPTION Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 m 4-SIP Module	PRESSURE TYPE	Differential
PACKAGE / CASE OUTPUT TYPE Wheatstone Bridge OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES DETAILED DESCRIPTION 4-SIP Module	PORT STYLE	Barbed
OUTPUT TYPE OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES DETAILED DESCRIPTION Wheatstone Bridge 40 mV ~ 95 mV 40 mV ~	PORT SIZE	Male - 0.19" (4.8mm) Tube, Dual
OUTPUT 40 mV ~ 95 mV OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Temperature Compensated DETAILED DESCRIPTION 40 mV ~ 95 mV 10 mV ~ 95 mV	PACKAGE / CASE	4-SIP Module
OPERATING TEMPERATURE -40°C ~ 85°C OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and the sensor 1	OUTPUT TYPE	Wheatstone Bridge
OPERATING PRESSURE 15 PSI (103.42 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic sensor 15 PSI (103.42 kPa) Differential Mal	OUTPUT	40 mV ~ 95 mV
MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 30 PSI (206.84 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 mages and 4-SIP Module	OPERATING TEMPERATURE	-40°C ~ 85°C
MAXIMUM PRESSURE 30 PSI (206.84 kPa) Lead free / RoHS Compliant FEATURES Temperature Compensated DETAILED DESCRIPTION 30 PSI (206.84 kPa) Lead free / RoHS Compliant Temperature Compensated Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic description 4-SIP Module	OPERATING PRESSURE	15 PSI (103.42 kPa)
LEAD FREE STATUS / ROHS STATUS FEATURES Temperature Compensated DETAILED DESCRIPTION Lead free / RoHS Compliant Temperature Compensated Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic description 4-SIP Module	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
Temperature Compensated DETAILED DESCRIPTION Temperature Compensated Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 magnetic description (4.8mm) Tube, Dual 40 mV	MAXIMUM PRESSURE	30 PSI (206.84 kPa)
DETAILED DESCRIPTION Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV ~ 95 rd 4-SIP Module	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
4-SIP Module	FEATURES	Temperature Compensated
ACCURACY ±0.5%	DETAILED DESCRIPTION	Pressure Sensor 15 PSI (103.42 kPa) Differential Male - 0.19" (4.8mm) Tube, Dual 40 mV \sim 95 mV 4-SIP Module
	ACCURACY	±0.5%

Related Tags

Honeywell Sensing and Productivity Solutions SCC15DN	SCC15DN Distributor	SCC15DN Supplior
Honeywell Sensing and Productivity Solutions Sections	SCC13DIN DIStributor	SCC15DN Supplier
SCC15DN Price	SCC15DN Pictures	SCC15DN Image
SCC15DN PDF Datasheet	SCC15DN Download Datasheet	SCC15DN Datasheet
SCC15DN Stock	Buy SCC15DN	Buy Honeywell Sensing and Productivity Solutions SCC15DN
Honeywell Sensing and Productivity Solutions SCC15DN	Honeywell Sensing and Productivity Solutions Supplier	Honeywell Sensing and Productivity Solutions Distributo
Honeywell Sensing and Productivity Solutions SCC15DN	HONEYWELL SCC15DN	Honeywell Sensing and Control EMEA SCC15DN
Honeywell Sensing and Productivity Solutions T&M		

Related Products



SCC15DN

SCC2230-D08-05

Manufacturers: Murata Electronics Description: IMU ACCEL/GYRO 3-AXIS SPI In stock: 1366 pcs

RFQ



SCC15DD4

Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR PRESS DIFF 15PSI

In stock: 6549 pcs

RFQ



SCC15GSMT

Manufacturers: Honeywell Sensing and Productivity Solutions Description: JZ SILICON PRESSURE PRODUCTS

In stock: 3323 pcs

RFQ



SCC15DP1

Manufacturers: Honeywell Sensing and Productivity Solutions Description: SCC DIFF GAUGE 0 PSID TO 15 PSID

In stock: 3348 pcs

RFQ



SCC15GD2

Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR PRESS GAUGE 15PSI

In stock: 4981 pcs

RFQ

Honeywell

SCC15AD2

Manufacturers: Honeywell Sensing and Productivity Solutions Description: SCC ABS 0 PSIA TO 15 PSIA

In stock: 5067 pcs

RFQ



SCC15ASMT

Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR ABSOLUTE 0-15PSIA SMT In stock: 2137 pcs

RFQ



SCC2130-D08-05

Manufacturers: Murata Electronics Description: IMU ACCEL/GYRO 3-AXIS SPI In stock: 922 pcs

Description: SCC ABS 0 PSIA TO 15 PSIA

RFQ



SCC190EFG

Manufacturers: Fluke Electronics Description: CABLE CARRYING CASE & SOFTWARE

In stock: 138 pcs

RFQ



SCC15AD4 Manufacturers: Honeywell Sensing and Productivity Solutions

In stock: 4092 pcs



SCC15AN Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SCC ABS 0 PSIA TO 15 PSIA In stock: 5999 pcs

RFQ



SCC15D

RFQ

Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SENSOR PRESS DIFF 15PSI In stock: 5946 pcs

RFQ

Copyright © 2020 Reliable Distributor of Electronic Components











